

1 LOCATION OF WATER WELL: County: Sedgwick	Fraction NW 1/4 NW 1/4 SE 1/4	Section Number 27	Township Number T 28 S	Range Number R 1 E
--	---	-----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

2000 Feet West of Hoover Road Near South End of Garvey Grain Elevators, Wichita, Kansas

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	Vulcan Chemicals 6200 South Ridge Road Wichita, Kansas 67215	01968023 MW-C Deep Board of Agriculture, Division of Water Resources Application Number:
---	---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 108 ft. ELEVATION: Approx Surface 1300
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr 11/20/96 Pump test data: Well water was N/A ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.25 in. to 108 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Stainless Steel
2 PVC	4 ABS	7 Fiberglass	Welded Threaded X
Blank casing diameter 2 in. to 93 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. 316			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 93 ft. to 108 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 91 ft. to 108 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 89 ft., From 89 ft. to 91 ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

Direction from well?		How many feet?	
FROM	TO	LITHOLOGIC LOG	PLUGGING INTERVALS
0	17	Brown, Lean to Fat Clay	
17	38	Brown, Fine to Medium Sand	
38	47	Brown, Lean to Fat Clay	
47	54	Brown, Fine to Medium Sand	
54	74	Brown, Lean to Fat Clay	
74	83	Brown, Fine to Medium Sand	
83	106	Brown Silty, Sandy Clay	
106	108	Weathered Shale	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/11/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11/11/96 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve Fischer</i>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.