


LOCATION OF WATER WELL: Fraction S N E W Section Number 11 Township Number 28 Range Number 1 SW
 County: Sedgewick
 Distance and direction from nearest town or city street address of well if located within city?

WATER WELL OWNER: Asphalt Co., Inc. 3511 South West Street
 R#, St. Address, Box #: 3511 S. West St.
 City, State, ZIP Code: Wichita, KS 67217 Board of Agriculture, Division of Water Resources
 Application Number: MUS

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 2018 DEPTH OF COMPLETED WELL: 2018 ft. ELEVATION: 1289.55



Depth(s) Groundwater Encountered 1. 10.0 ft. 2. 11.61 ft. 3. 11.61 ft.

WELL'S STATIC WATER LEVEL 11.61 ft. below land surface measured on mo/day/yr 11/6/98

Pump test data: Well water was 11.61 ft. after 11.61 hours pumping 11.61 gpm

Est. Yield 11.61 gpm: Well water was 11.61 ft. after 11.61 hours pumping 11.61 gpm

Bore Hole Diameter 8 in. to 20 ft., and 20 in. to 20 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:

5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

2 PVC 4 ABS 7 Fiberglass 7 PVC

Blank casing diameter 2 in. to 5 ft., Dia 5 in. to 5 ft., Dia 5 in. to 5 ft.

Casing height above land surface Flush in., weight Flush lbs./ft. Wall thickness or gauge No. Flush

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From 3 ft. to 5 ft.

From 10 ft. to 20 ft., From 3 ft. to 5 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 20 ft., From 3 ft. to 5 ft.

From 10 ft. to 20 ft., From 3 ft. to 5 ft.

GROUT MATERIAL: 2 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 2 ft. to 1 ft., From 1 ft. to 1 ft., From 1 ft. to 1 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? Northwest 13 Insecticide storage

How many feet? 30

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

6" 20' Sand

RECEIVED

MAR 23 1999

BUREAU OF WATER

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-3-98 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 634 This Water Well Record was completed on (mo/day/year) 11-25-98

Under the business name of Shirley E. W. Testa LLC by (signature) Shirley E. W. Testa