

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																																																																					
County: Sedgwick		SW 1/4 NW 1/4 SW 1/4		28		T 28 S		R 1 E (W)																																																																																					
Distance and direction from nearest town or city street address of well if located within city? Approximately 2 miles north of Bayneville																																																																																													
2 WATER WELL OWNER: Vulcan Materials Company RR#, St. Address, Box # : P.O. Box 12283 City, State, ZIP Code : Wichita, KS 67277 Board of Agriculture, Division of Water Resources Application Number:																																																																																													
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 124 ft. ELEVATION: unknown																																																																																										
			Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. ft. WELL'S STATIC WATER LEVEL 42.29 ft. below land surface measured on mo/day/yr 5-15-01 Pump test data: Well water was not checked ft. after hours pumping gpm Est. Yield unknown gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 126 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Test Well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒																																																																																										
			5 TYPE OF BLANK CASING USED:																																																																																										
			1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 102 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 24 in., weight 2.36 lbs./ft. Wall thickness or gauge No .214																																																																																										
			TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)																																																																																										
			SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft.																																																																																										
SCREEN-PERFORATED INTERVALS: From 102 ft. to 122 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 93 ft. to 126 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																																													
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug																																																																																													
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 93 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None known Direction from well? How many feet?																																																																																													
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr><td>0</td><td>5</td><td>Topsoil</td><td></td><td></td><td></td></tr> <tr><td>5</td><td>8</td><td>Clay, dark gray</td><td></td><td></td><td></td></tr> <tr><td>8</td><td>14</td><td>Clay, brown</td><td></td><td></td><td></td></tr> <tr><td>14</td><td>36</td><td>Sand and gravel, medium, fine</td><td></td><td></td><td></td></tr> <tr><td>36</td><td>46</td><td>Clay, brown</td><td></td><td></td><td></td></tr> <tr><td>46</td><td>57</td><td>Sand and gravel, medium, fine, very fine</td><td></td><td></td><td></td></tr> <tr><td>57</td><td>81</td><td>Clay, dark gray</td><td></td><td></td><td></td></tr> <tr><td>81</td><td>87</td><td>Clay, brown</td><td></td><td></td><td></td></tr> <tr><td>87</td><td>122</td><td>Sand and gravel, medium, fine, very fine, clay streak at 111' and 117'</td><td></td><td></td><td></td></tr> <tr><td>122</td><td>126</td><td>Limestone, hard</td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>										FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	5	Topsoil				5	8	Clay, dark gray				8	14	Clay, brown				14	36	Sand and gravel, medium, fine				36	46	Clay, brown				46	57	Sand and gravel, medium, fine, very fine				57	81	Clay, dark gray				81	87	Clay, brown				87	122	Sand and gravel, medium, fine, very fine, clay streak at 111' and 117'				122	126	Limestone, hard																					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																								
0	5	Topsoil																																																																																											
5	8	Clay, dark gray																																																																																											
8	14	Clay, brown																																																																																											
14	36	Sand and gravel, medium, fine																																																																																											
36	46	Clay, brown																																																																																											
46	57	Sand and gravel, medium, fine, very fine																																																																																											
57	81	Clay, dark gray																																																																																											
81	87	Clay, brown																																																																																											
87	122	Sand and gravel, medium, fine, very fine, clay streak at 111' and 117'																																																																																											
122	126	Limestone, hard																																																																																											
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-15-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 5-18-01 under the business name of Clarke Well & Equipment, Inc. by (signature)																																																																																													
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.																																																																																													