

1 LOCATION OF WATER WELL: County: Sedgwick NE 1/4 NE 1/4 NE 1/4 Section Number 12 Township Number T 28 S Range Number R 10

Distance and direction from nearest town or city street address of well if located within city? 2433 W 31st Wichita (Supply)

2 WATER WELL OWNER: Randy Wills Const. RR#, St. Address, Box #: 1574 Country Lane City, State, ZIP Code: Wichita, Kansas 67110 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section]

4 DEPTH OF COMPLETED WELL: Depth(s) Groundwater Encountered 1. 12 ft. 2. 7301 ft. WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 7301

Pump test data: Well water was 11 in. to 48 ft. after 48 hours pumping 48 gpm

Est. Yield 27 gpm Well water was 11 in. to 48 ft. after 48 hours pumping 48 gpm

Bore Hole Diameter 11 in. to 48 ft. and 11 in. to 48 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 12 Other (Specify below)

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 P/C 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded

Blank casing diameter 5 in. to 38 ft. Dia 2.40 in. to 160 psi

Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160 psi

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 38 ft. to 48 ft. From 12 ft. to 48 ft. From 0 ft. to 48 ft.

GRAVEL PACK INTERVALS: From 12 ft. to 48 ft. From 0 ft. to 48 ft. From 0 ft. to 48 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 12 ft. From 0 ft. to 48 ft. From 0 ft. to 48 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? northeast How many feet? 50

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 8 clay

8 47 sand

47 48 shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-3-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-3-01 under the business name of Wenzel Drilling Inc. by signature: Michael Grogg

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-236-5545. Send one to WATER WELL OWNER and retain one for your records.