

1 LOCATION OF WATER WELL:		WATER WELL RECORD		TOWNSHIP NUMBER		RANGE NUMBER	
County: Sedgwick		Fraction: SE 1/4 SE 1/4 NE 1/4		Section Number: 8		Township Number: T 28 S	
Distance and direction from nearest town or city street address of well if located within city?		Range Number: R 1 EW					
71 ft from East line of NE 1/4 of Section							
2 WATER WELL OWNER:		Kansas Corporation Commission					
RR#, St. Address, Box #		130 S. Market Rm 2125		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code		Wichita KS 67207		Application Number:			
3 LOCATE WELL'S LOCATION WITH:		4 DEPTH OF COMPLETED WELL:		5 ELEVATION:			
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered		1. 13 ft. 2. ft. 3. ft.			
WELL'S STATIC WATER LEVEL		ft. below land surface measured on mo/day/yr					
Pump test data: Well water was		ft. after		hours pumping gpm			
Est. Yield gpm: Well water was		ft. after		hours pumping gpm			
Bore Hole Diameter		8.5 in. to 24		ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well	
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering	
2 Irrigation		4 Industrial		7 Domestic (lawn & garden)		10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes. No. X		If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued. Clamped.	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)	
2 PVC		4 ABS		7 Fiberglass		Welded Threaded Flush	
Blank casing diameter		2 in. to 14		ft. Dia		in. to ft. Dia	
Casing height above land surface		Flush		in. weight		70.3 lbs./ft. Wall thickness or gauge No. Sch 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass		8 RMP (SR)		10 Asbestos-cement	
1 Steel		3 Stainless steel		6 Concrete tile		9 ABS	
2 Brass		4 Galvanized steel		5 Gauzed wrapped		8 Saw cut	
SCREEN OR PERFORATION OPENINGS ARE:		3 Mill slot		6 Wire wrapped		9 Drilled holes	
1 Continuous slot		4 Key punched		7 Torch cut		10 Other (specify)	
2 Louvered shutter		14		ft. to 24		ft. to ft.	
SCREEN-PERFORATED INTERVALS:		From		ft. to		ft. to ft.	
GRAVEL PACK INTERVALS:		From 10		ft. to 24		ft. to ft.	
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From		2		ft. to 10		ft. to ft.	
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well			
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage	
Direction from well?		How many feet?					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS					
0 2.5 Sandy Silt, dk br							
2.5 6 Silty Clay, br.							
6 13.5 Sandy Clay - reddish br.							
13.5 22.5 Sand - M to V grain							
22.5 24 Clay - grey to yellowish tan							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was		(1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)		4/30/02			
Water Well Contractor's Licence No.		531		This Water Well Record was completed on (mo/day/yr)			
under the business name of		Geotechnical Services, Inc.		by (signature) Allison M. Smith			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.							