

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE 1/4 SW 1/4 SW 1/4	2	T 28 S	R 1 E (W)
Distance and direction from nearest town or city street address of well if located within city? 3066 South Hoover Road, Wichita, Kansas					
2 WATER WELL OWNER: H&R Parts Company					
RR#, St. Address, Box #: 3066 South Hoover Road			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Wichita, Kansas 67215			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 1294.87 TOC			
		Depth(s) Groundwater Encountered 1. 16 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 03/05/02			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 26.5 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes (No) ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes (No)			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
(2) PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded X
Blank casing diameter 2 in. to 11.5 ft., Dia					
Casing height above land surface 4 in., weight					lbs./ft. Wall thickness or gauge No. Schedule 40
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		(3) Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 11.5 ft. to 26.5 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 9.5 ft. to 26.5 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (3) Bentonite 4 Other					
Grout intervals: From 1 ft. to 9.5 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	(16) Other (specify below)
				13 Insecticide storage	GW Contamination
Direction from well? South				How many feet? 50	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	11	Silty Clay			
11	16	Sandy Clay			
16	18	Clayey Sand			
18	21	Fat Clay			
	26.5	BOB			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/04/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 03/18/02 under the business name of Terracon by (signature) <i>Steve Fisher</i>					