

1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE 1/4 NW 1/4 NW 1/4	36	T 28 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city?					
From Haysville KS: 1 mile North + 3/4 mile West					
2] WATER WELL OWNER: John Hay					
RR#, St. Address, Box #: 3705 W 63rd St South					
City, State, ZIP Code: Wichita, KS 67215					
Board of Agriculture, Division of Water Resources					
Application Number: 1660					
3] LOCATE WELL'S LOCATION WITH 4] DEPTH OF COMPLETED WELL: 57 ft. ELEVATION:					
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. 42 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 42 ft. below land surface measured on mo/day/yr 12-14-02			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 300 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 30 in. to 57 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5] TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued. X Clamped.
PVC		4 ABS	7 Fiberglass		Welded.
Blank casing diameter 16 in. to 42 ft., Dia					Threaded.
Casing height above land surface 12 in., weight 16 lbs./ft.					Wall thickness or gauge No. 12"
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		2 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From 42 ft. to 57 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 57 ft., From ft. to ft.					
6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 28 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	12 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	
Direction from well? South				How many feet? 15	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	3	Topsoil			
3	15	Clay			
15	32	Medium Gravel w/ clay			
32	54	Medium Gravel			
54	57	Shale			
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-13-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 238 This Water Well Record was completed on (mo/day/yr) 1-7-03 under the business name of Weninger Irrigation by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					