

LOCATION OF WATER WELL: Sedgwick		FRACTION SW 1/4 NE 1/4 SE 1/4	SECTION NUMBER 10	TOWNSHIP NUMBER T 28 S	RANGE NUMBER R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 5801 W. Juno Wichita, Kansas					
WATER WELL OWNER: PURVINE, Cora RR#, ST. ADDRESS, BOX #: 5801 W. Juno CITY, STATE: Wichita, Kansas ZIP CODE: Board of Agriculture, Division of Water Resource Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N NW ——— NE E SW ——— SE S 1 Mile W ————— E	DEPTH OF COMPLETED WELL: 70 ft. Depth of groundwater Encountered: _____ ft. ELEVATION: _____ ft. WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 6/25/03 Pump test data: Well water was _____ ft. after hours of pumping @ gpm Est. Yield: gpm Well water was _____ ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 70 ft. and _____ in. to _____ ft.				
	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply <u>7. Lawn and garden only</u> 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? <u>YES</u> NO				
	CASING JOINTS: <u>Glued</u> Threaded Welded Clamped TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) <u>2. PVC</u> 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Blank casing diameter 5 in. to 50 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., Weight: 2.35 lbs./ft. Wall thickness or gauge No. .214				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass <u>7. PVC</u> 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped <u>8. Saw cut</u> 10. Other (specify)					
SCREEN - PERFORATION INTERVAL From 50 ft. to 70 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 70 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
GROUT MATERIALS: 1. Neat cement <u>2. Cement Grout</u> 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well <u>2. Sewer lines</u> 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? South How many feet? 80					
From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	15	clay			
15	20	fine sand			
20	25	clay			
25	35	sandy clay			
35	40	clay			
40	50	fine red sand			
50	57	medium sand			
57	64	clay			
64	70	medium sand			
Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6-25-2003 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6-27-2003 under the business name of Harp Well & Pump Service Inc. by (signature) <i>J o d d S . Har p</i>					