

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>nw 1/4 nw 1/4 nw 1/4</u>	Section Number <u>5</u>	Township Number T <u>28S</u> S	Range Number R <u>1W</u> E/W
Distance and direction from nearest town or city street address of well if located within city? <u>2517 S. Denne</u>					
2 WATER WELL OWNER: <u>Darrin Brown</u> RR#, St. Address, Box # : <u>2517 S. Denne</u> City, State, ZIP Code : <u>Wichita, KS</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N X - NW - - NE - - SW - - SE - S		4 DEPTH OF COMPLETED WELL <u>122</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1 <u>61</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>61</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Domestic (lawn & garden)</u> 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED: 1 <u>Steel</u> 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>122</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>16</u> in., weight lbs./ft. Wall thickness or gauge No. <u>26</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 <u>PVC</u> 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 <u>Mill slot</u> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 <u>Key punched</u> 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From <u>62</u> ft. to <u>122</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>24</u> ft. to <u>122</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other Grout Intervals: From <u>4</u> ft. to <u>24</u> ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 <u>Watertight sewer lines</u> 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>East</u> How many feet? <u>25</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	16	clay			
16	23	green shale			
23	57	blue shale			
57	61	red shale			
61	66	limestone			
66	122	blue shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-25-04</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>611</u> This Water Well Record was completed on (mo/day/yr) <u>5-23-05</u> under the business name of <u>Chase Drilling</u> by (signature) <u>Rehax</u>					