

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 SE 1/4 SE 1/4	SECTION NUMBER 31	TOWNSHIP NUMBER T 28 S	RANGE NUMBER R 1W E/W
---	--	------------------------------------	---	--

Distance and direction from nearest town or city street address of well if located within city?
6941 S. 103 W. Clearwater, Kansas

2 WATER WELL OWNER: MATTIX, Scott RR#, ST. ADDRESS, BOX #: 6941 S. 103 W. CITY, STATE: Clearwater, Kansas	Board of Agriculture, Division of Water Resource ZIP CODE: Application Number:
--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: ft. Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/20/05 Pump test data: Well water was ft. after hours of pumping @ gpm Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Bore Hole Diameter 12 in. to 95 ft. and in. to ft.	9. Dewatering 11. Injection well 12. Other (Specify below) 7. Lawn and garden only 10. Monitoring well 8. Air conditioning 6. Oil field water supply 5. Public water supply 4. Industrial 3. Feedlot 2. Irrigation 1. Domestic
---	---

Was a chemical/bacteriological sample submitted to Department? **YES** **NO**
 Was Water Well Disinfected? **YES** **NO**

5 TYPE OF CASING USED: 1. Steel 2. PVC 3. RPM (SR) 4. ABS 5. Wrought Iron 6. Asbestos-Cement 7. Fiberglass 8. Concrete tile 9. Other (Specify below) SDR-26	CASING JOINTS: Glued Threaded Welded Clamped Blank casing diameter 5 in. to 75 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 12 in. Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214
--	---

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1. Steel 2. Brass 3. Stainless Steel 4. Galvanized 5. Fiberglass 6. Concrete Tile 7. PVC 8. RMP (SR) 9. ABS 10. Asbestos-Cement 11. Other (specify) 12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1. Continuous slot 2. Louvered shutter 3. Mill slot 4. Key punched 5. Gauzed wrapped 6. Wire wrapped 7. Torch cut 8. Saw cut 9. Drilled holes 10. Other (specify) 11. None (open hole)

SCREEN - PERFORATION INTERVAL From 75 ft. to 95 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 95 ft. From ft. to ft.	SCREEN - PERFORATION INTERVAL From ft. to ft. From ft. to ft. SCREEN - PERFORATION INTERVAL From ft. to ft. From ft. to ft.
---	--

6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 2. Sewer lines 3. Watertight sewer line 4. Lateral lines 5. Cess Pool 6. Seepage pit 7. Pit privy 8. Sewage lagoon 9. Feed yard 10. Livestock pens 11. Fuel storage 12. Fertilizer storage 13. Insecticide storage 14. Abandon water well 15. Oil well/Gas well 16. Other (specify below)	Direction from well? West How many feet? 100
--	---

From To LITHOLOGIC LOG 0 4 topsoil 4 75 clay 75 80 fine sand 80 83 clay 83 91 fine sand 91 95 shale	From To LITHOLOGIC LOG
--	---

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5/20/2005 Kansas Water Well Contractor's License No. 236 under the business name of Harp Well & Pump Service Inc.	and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 5/23/2005 by (signature) J o d d S. H a r p
--	--