Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NWSE SE 7 28 R 1W 1/4 Т S E/W Distance and direction from nearest town or city street address of well if located within city? 11007 W. Hollywood Wichita, Kansas CARTER, Stephen WATER WELL OWNER: Board of Agriculture, Division of Water Resource 11007 W. Hollywood RR#,ST. ADDRESS,BOX # Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 115 4 DEPTH OF COMPLETED WELL: **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 28 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm -MW NE Est. Yield: Well water was ft. after hours of pumping @ <u>υ</u> gpm gpm ₫ 12 Bore Hole Diameter to 115 ft. in. WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 5. Public water supply 7. Lawn and garden only SW 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) submitted NO 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC Blank casing diameter 5 95 Dia. to in to Dia in. to ft. 12 Casing height above land surface: in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 8. RMP (SR) 2. Brass 6. Concrete Tile 12. None used (open hole) 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE 3. Mill slot 5. Gauzed wrapped 1. Continuous slot 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 4. Key punched 6. Wire wrapped 10. Other (specify) SCREEN - PERFORATION INTERVAL 95 115 From to ft.. From ft. ft. From ft., From ft. to ft. 24 GRAVEL PACK INTERVALS: ft. to 115 From ft., From ft. to ft. ft. From to ft.. From ft. **GROUT MATERIALS:** 6 Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: 24 From ft.. From ft.. From ft What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit East How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τo From Тο O 3 topsoil 3 20 clay 20 41 fine sand 41 100 clav 100110 medium sand 110 grey shale 115

Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 12/9/2014 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year) 12/10/2014

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp