l Job No. 147296					F0	SH-13
	WATER WELL RECORD F					· · · · · · · · · · · · · · · · · · ·
OCATION OF WATER WE			on Number			
ty: Sedgwic	k SE ½ SW ½ SE rest town or city street address of well if located		7	т 28	S R 1	
nce and direction from nea th side of MacArthur	Rd., approx. 270' E of W dead end of	MacArthur,	east of S	outhwest Blvd \	Vichita	
ATER WELL OWNER: S	chulte Country Store	<u>.</u>				
St. Address. Box # : 1	1012 Southwest Blvd.			Board of Agriculture	e, Division of Water F	Resources
State ZIP Code : V	Vichita, KS 67215			Application Numbe	r:	
OCATE WELL'S LOCATOR	DEPTH OF COMPLETED WELL	35	# EIE\	ATION:	1329.77 (TOC)	
N "X" IN SECTION BOX:	Depth(s) Groundwater Encountered	1 23	^{11.} EEE'	2	ft. 3	ft.
	WELL'S STATIC WATER LEVEL	21.00 ft i	pelow TOC r	neasured on mo/day/vr	09/2	4/14
NW NE ·	Pump test data: Well water					
w	E Est. Yield gpm: Well water	er was	· f	after h	ours pumping	gpm
	Bore Hole Diameter 8.25 in to	35	·	ft. and	in. to	ft.
sw se	Bore Hole Diameter 8.25 in. to WELL WATER TO BE USED AS: 5 1 Domestic 3 Feed lot 6	Public water su	pply	8 Air conditioning	11 Injection wel	Ī
l x						
<u> </u>	2 Irrigation 4 Industrial 7					
3	Was a chemical/bacteriological sample	submitted to D				
	submitted		Wa	ter Well Disinfected?		
PE OF BLANK CASING	·		te tile		GluedClar	mped
	RMP (SR) 6 Asbestos-Ceme				Welded) L
	ABS 7 Fiberglass				THIOGECU	lush
casing diameter	2 in. to 20 ft., Dia	in. to		ft., Dia	in. to	ft.
ng height above land surfa	ce 0 in., weight	0.703	lbs./ft.	Wall thickness or gaug	je No. SCH	. 40
OF SCREEN OR PERF	DRATION MATERIAL:	7_	PVC	10 Asbestos	-cemenτ	
	Stainless steel 5 Fiberglass	8	RMP (SR)	11 Other (sp	ecify)	
2 Brass 4 EEN OR PERFORATION	Galvanized steel 6 Concrete tile	y Ized wrapped	ABS	8 Saw cut	ed (open hole) 11 None (or	en hole)
1 Continuous slot		e wrapped		9 Drilled holes	(1)	•
2 Louvered shutter		ch cut		10 Other (specify)		
REEN-PERFORATED INTE			ft. I	From	ft. to	ft.
	From ft. to		ft. I	rom	ft. to	ft.
GRAVEL PACK INTER	46	35	ft. 1	rom	ft. to	ft.
				From		
ROUT MATERIAL:	1 Neat cement 2 Cement grout		tonite	4 Other		
	1 ft. to 18 ft. From			ft. From	ft. to	ft.
it is the nearest source of p				tock pens	14 Abandoned wate	r well
1 Septic tank	4 Lateral lines 7 Pit prin	ry	11 Fuel		15 Oil well/ Gas wel	
2 Sewer lines	5 Cess pool 8 Sewag	je lagoon		-	16 Other (specify be	elow)
3 Watertight sewer lines	6 Seepage pit 9 Feedy	ard				
ction from well?		FRALC	How many		INC INTERVALE	
	DE LITHOLOGIC LOG Topsoil	FROM	то	PLUGG	SING INTERVALS	
0 1	Silty Clay, dark brown to brown to		†			
2 11	red brown, some fine sand					
	Sandy Clay, brown, fine sand, fine	to				
11 30	medium below 23'		 			
30 35	Clayey Sand, fine to medium grain	iea	 			
			 			
			 			
				Survey date: 10		
				Latitude: N 37°		
				Longitude: W 9	7~28′03.3 2 "	

completed on (mo/day/yr)

Water Well Contractor's License No.

Under the business name of

GSI Engineering, LLC

by (signature)

Water Well Record was completed on (mo/day/yr)

10/16/14

by (signature)

INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

and this record is true to the best of my knowledge and belief. Kansas