WATER WELL F		WWC-5	Div	vision of Wate	er				
Original Record		ge in Well Use		ources App. 1		Well ID	_		
1 LOCATION OF W		Fraction	ľ	ction Numbe					
County: Sedgwick		NE 1/4 NE 1/4 NW 1/4		6	T 28 S				
2 WELL OWNER: I		First:				d (if unknown, distance and			
Business: Lariat Co	direction from nearest town or intersection): If at owner's address, check here:								
Address: Address:			10906 W. A	0906 W. Atlantic Circle					
City:	State:		Wichita, KS						
3 LOCATE WELL	1								
WITH "X" IN		MPLETED WELL: ,							
SECTION BOX:	Depth(s) Groundwater Encountered: 1)			(uccinial degrees)					
N	2)				Tionida Datain — 1100 01 — 1110 00 — 1110 21				
	WELL'S STATIC WATER LEVEL:18				Source for Latitude/Longitude:				
		e, measured on (mo-day-		Grant make model					
NW NE	Pumn test data: Well y	vater was 22 f	yı <i>y</i>		(WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map				
W E	Pump test data: Well vafter1.5 hour	gpm		Online Mapper:					
1 1 1 1 1	Well	t.		- Online Mapper					
SW SE	after hours pumping gpm								
	Estimated Yield:50				ft. Ground Level TOC				
S	Bore Hole Diameter: .		Source:						
1 mile in. to ft.									
7 WELL WATER TO									
1. Domestic:		ater Supply: well ID		10. □ Oi	l Field Water Supply:	lease			
☐ Household ■ Lawn & Garden		ng: how many wells?		11. Test Hole: well ID					
Livestock	7. ☐ Aquifer Recharge: well ID								
2. Irrigation			12. Geothermal: how many bores?						
3. ☐ Feedlot					b) Open Loop Surface Discharge Inj. of Water				
4. Industrial	☐ Recovery		Actuation						
Water well disinfected? ■ Yes □ No 8 TYPE OF CASING USED: □ Steel ■ PVC □ Other									
Casing diameter 5	in to 60 a	Diameter	in to	O JOIN I S	: ■ Glued ☐ Clampe	a weided inreaded			
Casing diameter									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)									
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous Slot ■ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)									
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)									
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From									
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other.									
Grout Intervals: From		ft., From	ft. to	ft., From	ft. to	ft.			
Nearest source of possibl			_		_				
Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage									
Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well									
■ Watertight Sewer Lines									
Direction from well? .So	uth	Distance from we	 :112 75+		A	}			
10 FROM TO	LITHOLO		FROM	ТО		or PLUGGING INTERVALS	_		
0 1	Top Soil					The second in th	<u></u>		
	Clay		Ť				_		
	Fine Sand						_		
	Med Sand						_		
	Clay		<u> </u>						
- -	~·~J						_		
			Notes:	L					
			1						
			1						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged									
under my jurisdiction and was completed on (mo-day-year) .1/28/.16 and this record is true to the best of my knowledge and belief									
under my jurisdiction and was completed on (mo-day-year) .1/28/.16									
under the business name of Weninger Drilling LLC									
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,									
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.									
Visit us at http://www.kdheks	gov/waterwell/index.html		KSA 82a-12	12		Revised 7/10/2015			