Form WWC-5 WATER WELL RECORD KSA 82a-1212 SECTION NUMBER LOCATION OF WATER WELL: FRACTION TOWNSHIP NUMBER RANGE NUMBER SW 1/4 \mathbf{SW} Sedgwick SW 1/4 15 Т 28 S 1WE/W Distance and direction from nearest town or city street address of well if located within city? 6922 W 47th St. South Wichita, Kansas LOVE, Mike Construction WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: P.O.Box 7 ZIP CODE: 67147 Valley Center, Kansas CITY, STATE: Application Number: 70 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. 25 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ NW NE Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Ī Bore Hole Diameter 12 70 and in. ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SE 7. Lawn and garden only SW 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) YES submitted Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 50 Dia. Dia. in. to in. ft. to 12 2.35 Casing height above land surface: Weight: lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 5. Fiberglass 9. ABS 1. Steel 8. RMP (SR) 12. None used (open hole) Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 7. Torch cut 9. Drilled holes 11. None (open hole) 1 Continuous slot 5. Gauzed wrapped 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) 50 70 SCREEN - PERFORATION INTERVAL ft. From ft... From ft to ft. to ft., From From ft. ft. to 24 GRAVEL PACK INTERVALS: ft. 70 From to ft., From ft. ft. From ft . From ft. ft. **GROUT MATERIALS** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft., From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines None Yet 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? From Τо LITHOLOGIC LOG From Τо LITHOLOGIC LOG topsoil clay 23 50 fine sand 50 52 clay 52 <u>70</u> medium sand

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 12/31/16 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/5/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp