Form WWC-5 KSA 82a-1212 WATER WELL RECORD 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NW 1/4 1W NW NW 12 Т 28 S R E/W Sedgwick 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 3423 S. Knight Wichita, Kansas WATER WELL OWNER: VANDNER, Norman Board of Agriculture, Division of Water Resource 3423 S. Knight RR#,ST. ADDRESS,BOX #: Wichita, Kansas CITY, STATE: Application Number: ZIP CODE 48 **ELEVATION:** LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: ft. WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. N 12 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/12/17 Pump test data: Well water was ft. after hours of pumping @ gpm NW NEft. after hours of pumping @ gpm Est. Yield: Well water was Φ gpm 12 to 48 Ξ Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply . Lawn and garden only 9E-3. Feedlot SW 1. Domestic 12. Other (Specify below) 10. Monitoring well 8. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; if yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO S Was Water Well Disinfected? (YES) NO submitted 5 TYPE OF CASING USED CASING JOINTS: Glued Threaded 9. Other (Specify below) Fiberglass 5. Wrought Iron 3. RPM (SR) 1 Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4 ABS 5 38 Dia. ft., Dia. ft. Blank casing diameter in in. to Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 Casing height above land surface: in.. TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 6. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2 Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 1. Continuous slot 6. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped 38 48 SCREEN - PERFORATION INTERVAL From ft. to ft., From ft. ft. ft fl., From From to ft. ft. to 24 ft. to 48 GRAVEL PACK INTERVALS: ft., From ft From to ft. From ft. to ft. From ft. bentonite hole plug **GROUT MATERIALS:** Other 6 2. Cement Grout 3. Bentonite 1. Neat cement Grout Intervals: From 24 ft.. ft to ft., From ft What is the nearest source of possible contamination: 10 Livestock pens 13. Insecticide storage 15. Oil well/Gas well 7. Pit privy 4. Lateral lines 1. Septic tank 16. Other (specify below) 11. Fuel storage 14. Abandon water well 8. Sewage lagoon 2. Sewer lines 5. Cess Pool 3. Watertight sewer line 6. West 12. Fertilizer storage 9. Feed yard 6. Seepage pit How many feet? 20 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Tο From Τо tonsoil clay 3 10 28 10 fine sand 28 35 clav 35 48 medium sand Contractor's or Landowner's Certification: This water wall was 1. constructed 2, reconstructed or 3. plugged under my jurisdiction and

Contractor's or Landowner's Certification: This water wall was 1. constructed 2. reconstructed or 3. plugged under my jurisdict was completed on (mo/day/year) 5/12/17 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/15/17 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp