	WELL R		Form	WWC-5		ision of Water	i			
P	Record [ge in Well Use		ources App. N		Well ID		
		ATER WE	LL:	Fraction	1	ction Number	,			
	: SEDGWI			NW 1/4 NE 1/4 SW 5		6	T 28 S			
2 WELL Business: Address:	OWNER: L CMC NE\	ast Name: V HOMES I	INC.	First:	Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here:					
Address: PO BOX 226 City: GODDARD State: KS ZIP: 67052					2606 South Lark, Wichita, KS, 67215					
3 LOCATE WELL WITH "X" IN 4 DEPTH OF COMPLETED WELL:									grees)	
SECTIO				Encountered: 1)						
1	Į			3) ft., or 4) TER LEVEL:				84 🗆 NAD 83 🗀 NAI	D 27	
				e, measured on (mo-day	Bource for Editate Bongitude.				+	
NW	above land surface, measured on (mo-								,	
	Pump test data: Well water was					, _ , _ , _ ,				
w										
SW	SE	after		water wasrs pumping						
Estimated Yield:			gpm			6 Elevation:ft. ☐ Ground Level ☐ TO€				
S Bore Hole Diameter:			Diameter: .	11.5 in. to 50	ft. and	Source	Source:			
mile in. to ft. Uther										
7 WELL WATER TO BE USED AS: 1. Domestic: 5. \[Dublic Water Supply: well ID										
1. Domestic										
. —	☐ Household 6. ☐ Dewatering: how many we Lawn & Garden 7. ☐ Aquifer Recharge: well IE									
. —	☐ Livestock 8. ☐ Monitoring: well ID									
2. 🔲 Irrigation 9. Environmental Remediation: well										
	3. Feedlot Soil Vapo									
4. Industrial Recovery Injection 13. Other (specify):										
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ■ No If yes, date sample was submitted:										
Water well disinfected? ■ Yes □ No 8 TYPE OF CASING USED: □ Steel ■ PVC □ Other										
Casing diameter										
Casing height above land surface										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)										
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:										
☐ Continuous Slot ☐ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)										
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)										
SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft. From ft. to ft. from ft. to ft.										
GRAVEL PACK INTERVALS: From 22 ft. to 50 ft., From ft. to it., From ft. to it.										
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 1 ft. to 1 ft., From ft. to ft.										
Nearest sou □ Septic		le contamina	tion: Lateral Lin	es	г	Livestock Pe	ne 🗆 Ineact	ticide Storage		
Sewer		_	Cess Pool	☐ Sewage I		Fuel Storage	ns ⊟ mseci	doned Water Well		
■ Watertight Sewer Lines										
Other	(Specify)			Distance from						
10 FROM	TO TO		LITHOLO		FROM			it. or PLUGGING INTERV	7415	
0		TOP SOIL	LITHOLU	GIC LUG	TROW	10	LITTEO, LOG (CORE,)	JI I LOUGHOUNTERV	CLLA	
1	**************************************	CLAY								
20		MED GRAV	/EL							
40		CLAY								
Notes:										
	WELL ONLY									
11 CONTRACTORIS OR LANDONINERIS OF DITIFICATION TILL										
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed. Treconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) .10/12/2018 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 884 This Water Well Record was completed on mg-day-year) 1.1/2.1/2018										
under the business name of WENINGER DRILLING LLC. Signature Mail 1 white copy along with a fee of \$5 00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,										
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at http://www.kdneks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015										