	WATER WELL	RECORD F	orm WW	/C-5 K	SA 82a-1212				
1 LOCATION OF WATER WELL:	FRACTION	-	1,22,	ION NUMBER	l .		RANGE NU		
☐ Sedgwick	NE 1/4 SI		1/4	19	Т 28	S	R 1W	E/W_	
Distance and direction from nearest town or city street address of well if located within city? Exposition & McLean Blvd. Wichita, Kansas									
	HITA, CITY OF	ia, Kansas							
1-1	N. Main					ard of Agric	culture, Division of Wa		
I	nita, Kansas		ZII	CODE: 6	7202 Appli	cation Num	ber: 20190	0085	
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLETE	D WELL: 40) ft.		ELEVATION:				
WITH AN "X" IN SECTION BOX: De	pth of groundwater Enco	untered:	ft.			ft.		ft.	
	ELL'S STATIC WATER L	EVEL 15	FT. BELO	W LAND SU	RFACE MEASURED				
NWNE	Pump tes				ft. after		of pumping @ of pumping @	gpm gpm	
M Miles	Est. Yield: g	pm Well wa 12 in.	terwas to 4	0 ft.	ft. after and	in.	to	ft.	
	ELL WATER TO BE USE	ED AS:				Dewaterir	ng 11. Injec	tion well	
1 sw se 1	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only								
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well We a chamical leader of located and a supplied to Department? VES (NO); If yes, what mo/day/yr was sample									
,	Vas a chemical/bacteriologica ibmitted	al sample submitted to t	Department?	YES Was W	/ater Well Disinfected	. /	_	0	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASING	IOINTS: (Glued	Threaded	
1. Steel 3. RPM (SR) Welded Clamped									
2. PVC 4. ABS	6. Asbestos-Cem		iie		g D:-		4	ft.	
Blank casing diameter 8	in. to 20	ft., Dia.	in.	to	ft., Dia.		in. to	IL.	
Casing height above land surface: 12 in., Weight: 5.52 lbs. / ft. Wall thickness or gauge No332									
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill s	lot 5. Gauze	ed wrapped	7. To	rch cut	9. Drilled ho	les	11. None (o	pen hole)	
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)									
SCREEN - PERFORATION INTERVAL	From 20	0 ft. to	35	ft.,	From	ft.	to	ft.	
	From	ft. to	ı	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 2	4 ft. to	40	ft.,	From	ft.	to	ft.	
	From	ft. to)	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat	cement 2.	Cement Grout	3	B. Bentonite	Othe	r bent	onite hole plu	ıg	
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 20 ft.									
What is the nearest source of possible contamination: 1 Sentic tank 4 Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								as well	
1. Septic tank 4. Lateral lines 16. Other (specify below							ecify below)		
2. Sewer lines 5. Cess root None Apparent									
3. Watertight sewer line 6. Seepage pit 5. Feet yard 12. Fertilizer storage Direction from well? How many feet?									
From To	LITHOLOGIC LC)G	From	То	Lľ	THOLO	GIC LOG		
0 3 topsoil		,	ļ						
3 23 fine sand 23 40 medium sand			 						
25 77 11131411 3213									
			-	ļ					
			 						
			 						
			1						
			L	l					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 4/25/19 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/30/19									
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb									