	WATER WE	LL REC	ORD F	orm WV	VC-5 K	SA 82a-	1212				
1 LOCATION OF WATER WELL:	FRACTION	200 0			SECTION NUMBER		TOWNSHIP NUMBER		RANGE NUMBER		
Sedgwick	SW 1/4	SW 1/	4 SW	1/4	36	T	28 S		R 1W	E/W	
Distance and direction from nearest town or city			n city?								
862 S. Cattail Circle	Haysville, Kan										
	USMEYER C	ONSTRU	JCTION				Boar	d of Agriculture, [Division of Wa	ter Resource	
The second secon	B W York			_	6	7215					
	hita, Kansas			_	IP CODE: 6			tion Number:			
WITH AN "X" IN SECTION BOX:	DEPTH OF COMPL					ELEVATIO					
1	pth of groundwater I			ft			ft.			ft.	
	ELL'S STATIC WAT		25		OW LAND SU			N mo/day/yr:	6/5/2	0	
		p test data:	Well wa			ft. after		hours of pum		gpm	
E E	Est. Yield: Bore Hole Diameter	gpm 12	Well wa in.	ter was	65 4	ft. after		hours of pum		gpm	
	ELL WATER TO BE		111	10 (65 ft	. and		in.	to 11. Injecti	ft.	
			5. Public wa	ter supply	7. Lawn	and garden	only 9. De	watering	Other (Spe		
	2. Irrigation 4. I		6. Oil field w			nditioning		onitoring well	Cuioi (Opo	ony bolow,	
	Was a chemical/bacterio	ological sample	e submitted to I	Department?	YES	NO		If yes, what m			
	ıbmitted				Was \	Water Well D	isinfected?	YES	NC)	
5 TYPE OF CASING USED: 1. Steel 3. RPM (S	5. Wrought li	ron	7. Fiberglass	9. C	ther (Specify	y below)	CASING JO			hreaded	
2. PVC 4. ABS	6. Asbestos-	Cement	8. Concrete ti	ile SD	R-26			Welde	ed (Clamped	
Blank casing diameter 5	in. to 4	5 ft.,	Dia.	in.	to	ft.,	Dia.	in.	to	ft.	
Casing height above land surface:	12 in.,	,			bs. / ft.					16.	
TYPE OF SCREEN OR PERFORATION	****		Weight:	2.33	DS. / π.	VV	aii thickness	or gauge No.	.214		
1. Steel 3. Stainless Steel	5. Fiberglass	7	. PVC	9. A	ABS	11	. Other (spe	cify)			
2. Brass 4. Galvanized	6. Concrete Til	e 8	. RMP (SR)	10. A	Asbestos-Ce	ment 12	2. None used	(open hole)			
SCREEN OR PERFORATION OPENIN	GS ARE										
1. Continuous slot 3. Mill s		auzed wrap	ped	7. T c	orch cut	9.	Drilled hole:	s 11	. None (op	en hole)	
2. Louvered shutter 4. Key p		ire wrapped	•		w cut	10	Other (spec			,	
						10.	Other (Spec	'' y '			
SCREEN - PERFORATION INTERVAL	From	45 ft.	to		ft.,	From	ft	ř	to	ft.	
	From	ft.			ft.,	From	ft		to	ft.	
GRAVEL PACK INTERVALS:	From	24 ft.	to	65	ft.,	From	ft	ē	to	ft.	
	From	ft.	to)	ft.,	From	ft		to	ft.	
	cement	2. Cemen	t Grout		3. Bentonite	1	Other	bentonite	hole plug	5	
Grout Intervals: From	ft. to	ft.,	From	ft.	to	ft.	, From	n 4 ft.	to 2	4 ft.	
What is the nearest source of possible c 1. Septic tank 4. Latera	7	Pit privy	1	0. Livesto	k pens	13. Ins	ecticide sto	orage 15.	Oil well/Ga	s well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water						46	Other (spec				
3 Watertight sewer line 6. Seepa		Feed yard		12. Fertilize	-	14.740	andon wate	1 11011			
Direction from well? East	ige pit	ood jara			. Storage	Hov	w many feet?	? 10 ft. plu	•		
From To	LITHOLOGIC	LOG		From	То	1.0.		HOLOGIC			
0 3 topsoil								.0200.0			
3 23 clay											
23 41 fine sand					ļ						
41 65 fine sand											
				 	 						
					 						
				-							
				 							
					+						
7 Contractor's or Landowner's Certif	ication: This water w	vell was 1	constructed) 2. re	constructed	d or 3,	plugged	under m	ny jurisdiction	n and	
was completed on (mo/day/year)	6/5/2020	-	d this record	10000							
								CICIODO			
Kansas Water Well Contractor's Licer	over-10 (11000/10)		This water we		•			6/6/2020			
under the business name of Harp	Well and Pum	p Service	<u> </u>	by (si	ignature)		Toda	એS. મ	arp		