

1 LOCATION OF WATER WELL:		Fraction	Township Number	Range Number	
County: SEDGWICK	NW ¼ SE ¼	Section Number 1	T 28 S	R 1 E W	
Distance and direction from nearest town or city street address of well if located within city? 2938 S. CUSTER WICHITA KS. 67217					
2 WATER WELL OWNER: MARK THIESING		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 2938 S. CUSTER		Application Number:			
City, State, ZIP Code : WICHITA KS. (67217)					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N NW NE SW SE S E		4 DEPTH OF COMPLETED WELL... 26 ft. ELEVATION: Depth(s) Groundwater Encountered 1... 17 ft. WELL'S STATIC WATER LEVEL ... 17 ft. below land surface measured on mo/day/yr 9-25-83 . Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm. Est. Yield _____ gpm; Well water was _____ ft. after _____ hours pumping _____ gpm. Bore Hole Diameter... 9 in. to 17 ft., and 5 in. to 26 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No X..... If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) ② PVC 4 ABS		Blank casing diameter ... 5 in. to 20 ft., Dia.in. toft., Dia.in. toft. Casing height above land surface... 13 in., weightlbs./ft. Wall thickness or gauge No. S&P#40 .			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		CASING JOINTS: Glued . X Clamped Welded Threaded			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		11 None (open hole) 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From... 20 ft. to 26 ft., Fromft. toft. Fromft. toft., Fromft. toft.					
GRAVEL PACK INTERVALS: Fromft. toft., Fromft. toft. Fromft. toft., Fromft. toft.					
6 GROUT MATERIAL: 1 Neat cement ② Cement grout 3 Bentonite 4 Other		Grout Intervals: From... 0 ft. to 10 ft., Fromft. toft., Fromft. toft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ③ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		Direction from well? WEST How many feet? 60			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0 FT.	3 FT.	TOP SOIL			
3 FT.	6 FT.	CLAY			
6 FT.	18 FT.	FINE SAND			
18 FT.	24 FT.	MED SAND			
24 FT.	26 FT.	COARSE GRAVEL			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was(1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-26-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. A-1BA . This Water Well Record was completed on (mo/day/yr) 10-3-83 under the business name of A & B WATER WELL SERV. by (signature) <i>X Ronald E Manning</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					