

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	$\frac{1}{4}$ $\frac{1}{4}$ NE $\frac{1}{4}$	1	T 28 S	R 1 EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER:	Dondlinger & Sons Construction	MW#5	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	P.O.Box 398, 1206 E Lincoln		
City, State, ZIP Code :	Wichita, Ks 67211		Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7.5 in. to 70 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
2 PVC	4 ABS		Threaded
Blank casing diameter 2 in. to 10 ft., Dia.	6 Asbestos-Cement		
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40	7 Fiberglass		
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement	
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
SCREEN-PERFORATED INTERVALS: From 10 ft. to 70 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 7 ft. to 70 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 7 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	Unknown
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Topsoil			
1	3	Silt			
3	5	Clay - silty, brown			
5	12	Clay - gray			
12	60.5	Sand - gravel			
60.5	62.5	Shale - hard			
62.5	64.5	Shale - firm			
64.5	70	Shale - hard & soft			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-20-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 8-31-90 under the business name of GeoCore Services, Inc. by (signature) <i>Dan A. Kelly</i>
