

1) LOCATION OF WATER WELL: County: Sedgwick		Fraction <u>NE</u> <u>1/4</u> <u>NE</u> <u>1/4</u>		Section Number 1	Township Number T 28 S	Range Number R 1	EW
Distance and direction from nearest town or city street address of well if located within city? 3201 Casado				MW-4, Drilled 11-8-90			
2) WATER WELL OWNER: Dondlinger & sons Construction							
RR#, St. Address, Box # : 3201 Casado				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Wichita, Ks.				Application Number:			
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. 1.2 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 1.2 ft. below land surface measured on mo/day/yr 1.1-8-90. Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7. 5/8 in. to 6.5 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒					
5) TYPE OF BLANK CASING USED:							
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile	
2 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)	
Blank casing diameter 2 in. to 5 ft. Dia				7 Fiberglass		CASING JOINTS: Glued Clamped	
Casing height above land surface 0 in. weight						Welded Threaded ☒	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes	
				7 Torch cut		10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 65 ft. to 5 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 65 ft. to 5 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
6) GROUT MATERIAL:							
1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals: From 5 ft. to 0 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank		4 Lateral lines		7 Pit privy		10 Livestock pens	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		12 Fertilizer storage	
						13 Insecticide storage	
						14 Abandoned water well	
						15 Oil well/Gas well	
						16 Other (specify below)	
						Unknown	
Direction from well? How many feet?							
FROM		TO		LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS	
0		5		Clay-silty, Dk. brown			
5		8.5		Clay-silty, gray brown			
8.5		10		Clay-sandy, gray brown			
10		20		Sand-Lt. gray brown			
20		25		Sand-Lt. brown, fine		Completed at the surface	
25		30		Gravel-sandy, brown		with a water tight locking	
30		50		Gravel-sandy, coarse		cap and bolt down steel	
50		63		Gravel-sandy, brown		manhole cover.	
63		65		Shale - White			
65		65.5		Shale - gray, hard			
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-8-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2-28-91 under the business name of GeoCore Services, Inc. by (signature) [Signature]							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							