


LOCATION OF WATER WELL: County: SEDGWICK	Fraction NW 1/4 SW 1/4 SW 1/4	Section Number 2	Township Number T 28 S	Range Number R 1 W 1/2
--	---	----------------------------	----------------------------------	----------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3044 S. Hoover, Wichita, Ks.

WATER WELL OWNER: Quality Manufacturing	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 3158 S. Hoover	Application Number:
City, State, ZIP Code: Wichita, Ks.	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 17 ft. 2. 17 ft. 3. 17 ft.
	WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 9-30-81
	Pump test data: Well water was 11 ft. after 11 hours pumping 11 gpm
	Est. Yield 11 gpm: Well water was 11 ft. after 11 hours pumping 11 gpm
	Bore Hole Diameter 11 in. to 11 ft., and 11 in. to 11 ft.
	WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped X
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 40 ft. Dia			
Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 203			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut .06	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 40 ft. to 60 ft.		
GRAVEL PACK INTERVALS:	From 14 ft. to 60 ft.		

GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout intervals: From 4 ft. to 14 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				NONE APPARENT

Direction from well?	How many feet?
FROM TO LITHOLOGIC LOG	FROM TO LITHOLOGIC LOG
0 3 Topsoil	
3 14 Clay	
14 38 Fine Sand	
38 42 Clay	
42 60 Medium Sand and Clay Balls	

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-30-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 2-26-82
under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnold

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.