

1 LOCATION OF WATER WELL:		Fraction NW 1/4 NW 1/4 NW 1/4		Section Number 2	Township Number T 28 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 115 Feet South and 130 Feet East of Shop Building located at 2550 South Hoover Road, Wichita, KS 01928003 MW-2						
2 WATER WELL OWNER: W. B. Carter Construction Company, Inc. RR#, St. Address, Box #: 2550 South Hoover Road City, State, ZIP Code: Wichita, KS 67204						
Board of Agriculture, Division of Water Resources Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: Approximate Surface Elevation: 97.6 ft.				
		Depth(s) Groundwater Encountered 1. 11.6 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 11.6 ft. below land surface measured on mo/day/yr 02/13/92 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.2 in. to 25 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 9.5 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface -3 in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 9.5 ft. to 24.5 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 6.5 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 4.5 ft. From 4.5 ft. to 6.0 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0.0 5.0 Silty Sand; Brown 5.0 12.0 Fine to Medium Sand; Brown 12.0 14.0 Medium to Coarse Sand; Gray-Brown 14.0 25.0 Medium to Coarse Sand With Gravel; Gray-Brown						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 02/13/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 04/30/92 under the business name of Terracon Consultants SC, Inc. by (signature) [Signature]						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						