

1 LOCATION OF WATER WELL: County: Sedgwick NW 1/4 NW 1/4 SW 1/4 Section Number 7 Township Number 28 S Range Number 1 E Distance and direction from nearest town or city street address of well if located within city? 1/2 W 1/2 No Shulte Rs.

2 WATER WELL OWNER: Jerry Silvers 358 No Fern Wichita, KS 67203 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section of the SW quadrant]

4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 1123-81 ft. Depth(s) Groundwater Encountered: 1. 35 ft. 2. 39 ft. 3. 10 ft. WELL'S STATIC WATER LEVEL: 35 ft. below land surface measured on mo/day/yr Pump test data: Well water was 39 ft. after 12 hours pumping 10 gpm Est. Yield: 20 gpm Well water was 39 ft. after 12 hours pumping 10 gpm Bore Hole Diameter: 11 in. to 75 ft. and 11 in. to 75 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped Welded Threaded 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter: 5 in. to 40 ft. Dia 5 from 50-75 ft. Dia 1.59 lbs./ft. Wall thickness or gauge No SPR-26 Casing height above land surface: 12 in. weight 1.59 lbs./ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft. From 10 ft. to 75 ft. GRAVEL PACK INTERVALS: From 10 ft. to 75 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 6 ft. to 16 ft. From 16 ft. to 125 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? EAST How many feet? 125

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-23-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 1-7-82 under the business name of Kenneth Sully by (signature) Kenneth Sully

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.