

1] LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NW ¼ NE ¼ SW ¼	7	T 28 S	R 1 E	(M)
Distance and direction from nearest town or city street address of well if located within city? ½ N OF SCHULTE, KS					
2] WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : Medicine Lodge, Kansas		Lease: MOUNT A #1 Application Number:			
3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4] DEPTH OF COMPLETED WELL:			
		60 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 29 Nov. 83.			
		Pump test data: Well water was ft. after hours pumping gpm Est. Yield 35 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 60 in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
5] TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded			
Blank casing diameter 5 in. to 60 ft., Dia. Casing height above land surface 12 in., weight 2.34 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 60 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 60 ft., From ft. to ft.					
6] GROUT MATERIAL:		3 Bentonite 4 Other			
1 Neat cement 2 Cement grout					
Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage NONE					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Soil, top			
2	18	Clay, tan			
18	40	Sand, fine to coarse and fine to med gravel			
40	52	Clay, gray			
52	60	Shale, green and blue			
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 29 NOV 83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 14 FEB 84 under the business name of Central Well & Pump Inc. by (signature) J. J. Anomnick					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					