

1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 SW 1/4 Section Number 7 Township Number T 28 S Range Number R 1 E
 County: Sedgewick
 Distance and direction from nearest town or city street address of well if located within city?
335 No Anne Schulte

2 WATER WELL OWNER: St. Peter's Church
 RR#, St. Address, Box #: 335 N. Anne Schulte
 City, State, ZIP Code: 67215
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	E
	SW	<u>X</u> SE	
	S		

4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 4-16-83
 Depth(s) Groundwater Encountered 1. 24 ft. 2. 30 ft. 3. 4-16-83 ft.
 WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 30 ft. after 20 hours pumping 35-40 gpm
 Est. Yield 35-40 gpm: Well water was 30 ft. after 20 hours pumping 35-40 gpm
 Bore Hole Diameter 11 in. to 65 ft., and 65 in. to 65 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 8 Air conditioning ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 8 RMP (SR) ☐ 5 Wrought iron ☐ 6 Concrete tile ☐ CASING JOINTS: Glued X Clamped X
 2 PVC ☐ 4 ABS ☐ 7 Fiberglass ☐ 9 Other (specify below) ☐ Welded X
 Blank casing diameter 5 in. to 30 ft., Dia. 1.59 in. to 1.59 ft., Dia. 1.59 in. to 1.59 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge 50R-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐
 12 None used (open hole) ☐
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 10 Other (specify) ☐
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 65 ft., From 30 ft. to 65 ft., From 30 ft. to 65 ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 65 ft., From 15 ft. to 65 ft., From 15 ft. to 65 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
 Grout Intervals: From 3 ft. to 15 ft., From 3 ft. to 15 ft., From 3 ft. to 15 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? N.E. How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	23	Red clay			
23	31	fine sand			
31	32	clay			
32	48	Med gravel			
48	65	gray shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-16-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-1-83 under the business name of Wenger Dubley by (signature) Wenger Dubley

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.