

1 LOCATION OF WATER WELL: County: Sedgwick	Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 7	Township Number T 28 S	Range Number R 1 Y/W
--	----------------------------------	----------------------------	---------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

819.6'N & 695.8'W of SE corner Sec. 7

2 WATER WELL OWNER: Kansas Dept. of Health and Environment	SCHULTE MW04
RR#, St. Address, Box # Forbes Field, Bldg. 740	Board of Agriculture, Division of Water Resources
City, State, ZIP Code Topeka KS 66620	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 47.5 ft. ELEVATION: 1332.13 MSL TOC
	Depth(s) Groundwater Encountered 24.06 TOC ft. 2. TOC ft. 3 1329.71 GS ft.
	WELL'S STATIC WATER LEVEL 1308.07 ft. below land surface measured on mo/day/yr 091492
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 7.63 in. to 1282.2 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well MW04
	Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted Part of RFP 82095
	Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded XXX
Blank casing diameter 2 in. to ft., Dia			
Casing height above land surface 2.42 ft. weight 0.70 lbs./ft. Wall thickness or gauge No. Sch 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot 0.02	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From 1312.7 ft. to 1282.2 ft., From ft. to ft.			
GRAVEL PACK INTERVALS:			
From 1317.2 ft. to 1282.2 ft., From ft. to ft.			
+ natural			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other bentonite pellets
Grout Intervals:	From 1329.7 ft. to 1318.9 ft., From 1318.9 ft. to 1317.2 ft., From ft. to ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)

Direction from well?		How many feet?	
FROM	TO	FROM	TO
1329.7	1325.7		
1325.7	1316.7		
1316.7	1304.2		
1304.2	1287.2		
1287.2	1282.2		
LITHOLOGIC LOG		PLUGGING INTERVALS	
clay, gray topsoil		E Log 091692	
clay, sandy, brown		Sampled 091792	
sand, fine, some br. clay			
sand, F-M-C, with minor silty clay		Drilled 072892	
clay, brownish white, w/some gravel		steel protective cover	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 091692 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 020392 under the business name of Total Environmental Services/Technologies by (signature) <i>David Bimbley</i>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.