

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: SEDGWICK	NW 1/4 NW 1/4 NW 1/4	8	T 28 S	R 1 W E/W

Distance and direction from nearest town or city street address of well if located within city?

Approximately 31st and Maize Road Schulte, Kansas

2 WATER WELL OWNER:	Dugan Truck Lines, Inc.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	10200 West K-42 Highway	Application Number:
City, State, ZIP Code :	Schulte, Kansas	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 8-22-84.
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 11 in. to ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No XX ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes XX No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	11 Injection well
Blank casing diameter 5 in. to 65 ft., Dia			12 Other (Specify below)
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement
1 Steel	3 Stainless steel	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:		From 65 ft. to 80 ft.	From 80 ft. to 80 ft.
GRAVEL PACK INTERVALS:		From 14 ft. to 80 ft.	From 80 ft. to 80 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 4 ft. to 14 ft.	From 14 ft. to 14 ft.	From 14 ft. to 14 ft.	From 14 ft. to 14 ft.
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	None Apparent

Direction from well?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	26	Clay			
26	32	Fine Sand			
32	66	Clay			
66	80	Fine Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-22-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 2-21-85 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

28

R

END

SEC.

8

NW 1/4

NW 1/4

NW 1/4

NW 1/4

NW 1/4

NW 1/4