

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NW 1/4 SE 1/4 NW 1/4	8	T 28 S	R 1

Distance and direction from nearest town or city street address of well if located within city?

3472.0'N & 3857.4'W of SE corner Sec. 8

2 WATER WELL OWNER: Kansas Dept. of Health and Environment	SCHULTE TH12
RR#, St. Address, Box #: Forbes Field, Bldg. 740	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Topeka KS 66620	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 49 ft. ELEVATION: 1331.28 MSL TOC
	Depth(s) Groundwater Encountered 1. 25.15 TOC ft. 2. TOC ft. 3. 1329.78 GS ft.
	WELL'S STATIC WATER LEVEL 1306.13 ft. below land surface measured on mo/day/yr .091492
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 7.63 in. to 1280.8 ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Part of RFP 82095	
Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded
Blank casing diameter 2 in. to 1311.3 ft. Dia	0.70 lbs./ft. Wall thickness or gauge No. Sch 40		
Casing height above land surface 1.50 ft XX			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot 0.01	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From 1311.3 ft. to 1280.8 ft. From ft. to ft.			
GRAVEL PACK INTERVALS:			
From 1314.5 ft. to 1280.8 ft. From ft. to ft.			
NATURAL			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 1329.8 ft. to 1314 ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? How many feet?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
1329.8	1327.8	topsoil, sandy br. clay			E Log 091592
1327.8	1324.8	clay, sandy, grayish brown to tan			Sampled 091592
1324.8	1308.8	clay, sandy reddish brown to tan			
1308.8	1303.8	sand, & VF-F with clay			
1303.8	1287.2	sand, F-C brown			
1287.2	1280.8	clay, stiff, reddish brown			plugged casing and screen and plugged from 1314 to GS 1329.8 with 12 cu.ft bentonite grout

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 081992 Plugged 091592 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 020393 under the business name of Total Environmental Services/Technologies by (signature) Dwight Brinkley
--