


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE ¼ NW ¼ NE ¼	9	T 28 S	R 1 W E/W
Distance and direction from nearest town or city street address of well if located within city? 1924' West & 908' South of NE Corner of Sec. 9 Wichita, Kansas					
2 WATER WELL OWNER: The Atchinson, Topeka & Santa Fe Railway Co. RR#, St. Address, Box #: 920 S.E. Quincy St. Board of Agriculture, Division of Water Resources City, State, ZIP Code: Topeka, KS. 66628 Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 79 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 32.7 ft. below land surface measured on mo/day/yr 3-12-88			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter 4 1/2 in. to ft. and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well			
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)		Welded metal screws			
2 PVC 160 4 ABS 7 Fiberglass		Threaded			
Blank casing diameter 2 in. to 59 ft. Dia. in. to ft. Dia. in. to ft.		Casing height above land surface 24 in. weight 43 lbs./ft. Wall thickness or gauge No. .091			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 160 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes			
7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 59 ft. to 79 ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 40 ft. to 79 ft. From ft. to ft.		From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Holeplug					
Grout Intervals: From 0 ft. to 40 ft. From 79 ft. to 85 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage None apparent possible VOC'S					
Direction from well?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	15	Brown Clay			
15	20	Very Fine to Fine Sand with Tan Clay Mixed			
20	23	Fine to Coarse Sand, Fine to Coarse Gravel			
23	35	Gray Clay			
35	66	Fine to Coarse Sand, Fine to coarse Gravel, loose			
66	67	Tan Clay			
67	79	Fine to Coarse Sand, Fine to Coarse Gravel			
79	85	Gray Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-12-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-31-88 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks. underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					