


1 LOCATION OF WELL: County: Sedgwick Fraction: NW 1/4 NW 1/4 SW 1/4 Section Number: 9 Township Number: T 28 S Range Number: R 1 E/W
 Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: Ray Holt
 RR#, St. Address, Box #: 3050 S Tyler
 City, State, ZIP Code: Wichita KS
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 81 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 42 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 42 ft. below land surface measured on mo/day/yr 10-12-92
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter in. to ft. and in. to ft.
 WELL WATER TO BE USED AS:
☒ Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes ☒ No ☒

5 TYPE OF BLANK CASING USED:
☐ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued ☒ Clamped
☒ 2 PVC ☐ 5 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded
☐ 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 72 ft. Dia. in. to ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface 12 in. weight 2,600 lbs./ft. Wall thickness or gauge No. 160PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 72 ft. to 81 ft. From ft. to ft. From ft. to ft. From ft. to ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 81 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: ☒ 3 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 23 ft. to 23 ft. From ft. to ft. From ft. to ft. From ft. to ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? East How many feet? 150'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0	top soil			
2	18	clay			
18	38	sand med sand			
38	46	clay			
46	60	fine med sand			
60	81	med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 10-12-92 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-15-92
 under the business name of Weninger Drilling Inc by (signature) Susan H. Weninger