


1 LOCATION OF WATER WELL: County: Sedgwick Fraction: NW 1/4 NW 1/4 SW 1/4 Section Number: 10 Township Number: T 28 S Range Number: R 1 E W

Distance and direction from nearest town or city street address of well if located within city? See Below.

2 WATER WELL OWNER: Pearl Nash Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 8632 W. 36th St Application Number:
City, State, ZIP Code: WICHITA KS 67209

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 38 ft.

Depth(s) Groundwater Encountered: 1. 38 ft. 2. 38 ft. 3. 38 ft.

WELL'S STATIC WATER LEVEL: 38 ft. below land surface measured on mo/day/yr 8-14-91

Pump test data: Well water was 38 ft. after 12 hours pumping 20 gpm

Est. Yield: 60 gpm: Well water was 38 ft. after 12 hours pumping 20 gpm

Bore Hole Diameter: 11 in. to 65 ft., and 65 in. to 65 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS: Glued <u>X</u> Clamped
2 PVC	4 ABS	7 Fiberglass		Welded
				Threaded

Blank casing diameter: 5 in. to 58 ft., Dia. 58 in. to 58 ft., Dia. 58 in. to 58 ft., Dia. 58 in. to 58 ft.

Casing height above land surface: 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 58 ft. to 65 ft., From 58 ft. to 65 ft., From 58 ft. to 65 ft., From 58 ft. to 65 ft.

GRAVEL PACK INTERVALS: From 23 ft. to 65 ft., From 23 ft. to 65 ft., From 23 ft. to 65 ft., From 23 ft. to 65 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 23 ft., From 23 ft. to 65 ft., From 23 ft. to 65 ft., From 23 ft. to 65 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? North How many feet? 80

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	26	Clay			
26	41	fine SAND.			
41	42	Clay			
42	65	fine to med SAND.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-14-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 8-16-91 under the business name of Weningerschultz by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.