

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: SEDGWICK		NW 1/4 NW 1/4 SW 1/4		11		T 28 S		R 1 W /E/W	
Distance and direction from nearest town or city street address of well if located within city?									
3610 S. Hoover Ct., Wichita, Ks.									
2 WATER WELL OWNER: Richard Chebultz					Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box # : 3610 S. Hoover Ct.					Application Number:				
City, State, ZIP Code : Wichita, Ks.									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:				
					Depth(s) Groundwater Encountered 1. 32 ft. 2. ft. 3. ft.				
					WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr 3-19-82				
					Pump test data: Well water was ft. after hours pumping gpm				
					Est. Yield gpm: Well water was ft. after hours pumping gpm				
					Bore Hole Diameter 11 in. to ft., and in. to ft.				
					WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well				
					1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
					2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well				
					Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted				
					Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 5 in. to 38 ft. Dia in. to Cer-Mac Styrene SDR-26 in. to									
Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 203									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
3 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 38 ft. to 60 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 14 ft. to 60 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 4 ft. to 14 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? West How many feet? 12									
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG									
0 3 Topsoil									
3 29 Clay									
29 37 Fine Sand									
37 45 Clay									
45 60 Fine Sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-19-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-4-82 under the business name of Harp Well & Pump Serv., Inc. by (signature) M. Arnold									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									