

1 LOCATION OF WATER WELL: County: SEDGWICK	Fraction SW 1/4 NW 1/4 NW 1/4	Section Number 12	Township Number T 28 S	Range Number R 1 E
--	---	-----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3435 S. ILLINOIS WICHITA, KS 67217

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code	E. J. WILDER 3435 S ILLINOIS WICHITA, KS 67217	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 10 ft. 2. 10 ft. 3. 10 ft. WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 7-13-92 Pump test data: Well water was 10 ft. after 2 hours pumping 25 gpm Est. Yield 35 gpm Well water was 10 ft. after 2 hours pumping 25 gpm Bore Hole Diameter 6 in. to 32 ft. and 32 in. to 32 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No ☒

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped ☒
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded ☒
Blank casing diameter 2 in. to 26 ft., Dia 26 in. to 26 ft., Dia 26 in. to 26 ft.			Threaded ☒
Casing height above land surface 14 in., weight 14 lbs./ft. Wall thickness or gauge No. 167			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel	5 Gauzed wrapped	8 Saw cut
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	3 Mill slot	6 Wire wrapped
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 26 ft. to 32 ft., From 32 ft. to 32 ft., From 32 ft. to 32 ft.		
GRAVEL PACK INTERVALS:	From 10 ft. to 32 ft., From 32 ft. to 32 ft., From 32 ft. to 32 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well? South			13 Insecticide storage	16 Other (specify below)
			How many feet? 35	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	SANDY LOAM TOP SOIL			
2	16	FINE SAND			
16	32	COURSE SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-13-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 7-14-92 under the business name of RALPH METZGER WELL DRILLING
--