

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE 1/4 NE 1/4 SE 1/4		12		T 28 S		R 1W EW	
Distance and direction from nearest town or city street address of well if located within city?									
Bethel Life Center Bypass and Meridian Wichita, Ks. 3777 So. Meridian									
2 WATER WELL OWNER:		Bethel Life Center, INC							
RR#, St. Address, Box # :		3777 So. Meridian							
City, State, ZIP Code :		Wichita, Ks.							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 4-21-89							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 11 in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile							
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)							
5		7 Fiberglass Cer-Mac styrene SDR-26							
Blank casing diameter in. to 30 ft., Dia in. to ft., Dia in. to ft.		Welded							
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203		Threaded							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)							
2 Louvered shutter 4 Key punched 7 Torch cut									
SCREEN-PERFORATED INTERVALS: From 30 ft. to 50 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 24 ft. to 50 ft., From ft. to ft.									
6 GROUT MATERIAL:		2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard									
Direction from well? None		How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 Topsoil									
3 17 Clay									
17 27 Fine Sand									
27 50 Medium Sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-21-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-15-89 under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									