

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: SW 1/4 NW 1/4 NW 1/4 Section Number: 13 Township Number: T 28 S Range Number: R 1 E(10) Distance and direction from nearest town or city street address of well if located within city? 4124 S. WEST ST. WICHITA, KS 1/4 mile S. OF Wichita city Limit

2 WATER WELL OWNER: John DEARTH RR#, St. Address, Box #: 4124 S. WEST ST City, State, ZIP Code: WICHITA, Kansas 67217 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section of the top-left 4-section block]

4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: 16 ft. Depth(s) Groundwater Encountered: 1. 16 ft. 2. 2 ft. 3. 25 ft. WELL'S STATIC WATER LEVEL: 16 ft. below land surface measured on mo/day/yr NOV 3-82 Pump test data: Well water was 40 gpm 16 ft. after 2 hours pumping 25 gpm Est. Yield 40 gpm Well water was 48 ft. after 2 hours pumping 25 gpm Bore Hole Diameter: 5 in. to 48 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter: 2 in. to 38 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 12 in., weight 1 lbs./ft. Wall thickness or gauge No. 167 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 38 ft. to 48 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 10 ft. to 48 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage SAND POINT WELL IN USE Direction from well? South How many feet? 12

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-3-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 10-29-82 under the business name of RALPH THETZLER WELL DIGGER DRILLING (signature) Ralph S. Thetzler INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underlining or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.