


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: County <u>Sedgwick</u>		Fraction <u>1/4 NE 1/4 NW 1/4</u>	Section number <u>16</u>	Township number <u>28</u>	Range number <u>1</u>
2. Distance and direction from nearest town or city: <u>1/2 E of Tyler Road, on</u>		3. Owner of well: <u>Paul Gyrrens</u>			
Street address of well location if in city: <u>39th St. So on</u>		R.R. or street: <u>3360 South Tyler Rd.</u>			
City, state, zip code: <u>Wichita, Kansas</u>					
4. Locate with "X" in section below: 		Sketch map: <u>South Side of Rd. Wichita, Kansas.</u>			
5. Type and color of material		From	To	6. Bore hole dia. <u>11</u> in. Completion date <u>8-26-75</u>	
<u>Sandy Soil</u>		<u>0</u>	<u>2</u>	Well depth <u>80</u> ft.	
<u>Red Clay</u>		<u>2</u>	<u>10</u>	7. ☐ Cable tool ☒ Rotary ☐ Driven ☐ Dug	
<u>Fine Sand</u>		<u>10</u>	<u>20</u>	☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
<u>Medium Sand and Clay</u>		<u>20</u>	<u>45</u>	8. Use: ☒ Domestic ☐ Public supply ☐ Industry	
<u>Medium Sand</u>		<u>45</u>	<u>80</u>	☐ Irrigation ☐ Air conditioning ☐ Stock	
				☐ Lawn ☐ Oil field water ☐ Other	
				9. Casing: Material <u>styrofoam</u> Height: Above or below	
				Threaded ☐ Welded ☒ Surface <u>12</u> in.	
				RMP ☒ PVC ☐ Weight <u>12</u> lbs./ft.	
				Dia. <u>5</u> in. to <u>80</u> ft. depth Wall Thickness: inches or	
				Dia. <u>5</u> in. to <u>80</u> ft. depth gage No. <u>20</u>	
				10. Screen: Manufacturer's name <u>Sunflower</u> Plastic	
				Type <u>styrofoam</u> Dia. <u>5</u> in.	
				Slot/gauze <u>005</u> Length <u>30</u> ft.	
				Set between <u>50</u> ft. and <u>80</u> ft.	
				Gravel pack? <u>yes</u> Size range of material <u>1/4-1/8</u> in.	
				11. Static water level: <u>31</u> ft. below land surface Date <u>8-26-75</u>	
				12. Pumping level below land surfaces:	
				<u>31</u> ft. after <u>12</u> hrs. pumping <u>236</u> g.p.m.	
				<u>31</u> ft. after <u>12</u> hrs. pumping <u>236</u> g.p.m.	
				Estimated maximum yield <u>236</u> g.p.m.	
				13. Water sample submitted: <u>no</u> mo./day/yr.	
				Yes ☐ No ☒ Date <u>8-26-75</u>	
				14. Well head completion:	
				☒ Pitless adapter <u>12</u> inches above grade	
				15. Well grouted? <u>yes</u>	
				With: ☒ Neat cement ☐ Bentonite ☐ Concrete	
				Depth: From <u>40</u> ft. to <u>14</u> ft.	
				16. Nearest source of possible contamination: <u>none</u>	
				ft. <u>0</u> Direction <u>0</u> Type <u>0</u>	
				Well disinfected upon completion? ☒ Yes ☐ No	
				17. Pump: <u>Not installed</u>	
				Manufacturer's name <u>Hydraulic Prod. Co.</u>	
				Model number <u>608420</u> HP <u>2</u> Volts <u>230</u>	
				Length of drop pipe <u>40</u> ft. capacity <u>50</u> g.p.m.	
				Type: ☒ Submersible ☐ Turbine	
				☐ Jet ☐ Reciprocating	
				☐ Centrifugal ☐ Other	
18. Elevation:		19. Remarks:		20. Water well contractor's certification:	
Topography: ☒ Hill ☐ Slope ☐ Upland ☐ Valley		<u>This well is to used to fill a pond only.</u>		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.	
				Business name <u>Sharp Well Pump</u> License No. <u>236</u>	
				Address <u>Wichita, Kansas</u>	
				Signed <u>M. Arnold</u> Date <u>8-27-75</u>	
				Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5