

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Sedgwick	Fraction $\frac{E\frac{1}{2}}{1/4 \quad 1/4 \text{ NW} \quad 1/4}$	Section number 16	Township number T 28 S R 1	Range number E W
2. Distance and direction from nearest town or city: 4 miles West of Wichita, KS Street address of well location if in city:			3. Owner of well: Vulcan Materials Co. R.R. or street: 6200 So. Ridge Road City, state, zip code: Wichita, KS 67201		
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile			Sketch map: 1320' South & 1450' East of the NW Corner of Sec. 16 Lauer #2		
5. Type and color of material			From	To	
Top soil			0	3	
Brown & red clay & gravel streak at 19'			3	21	
Yellow clay			21	27	
Sand & gravel			27	60	
Sand, gravel & clay streaks			60	73	
Sand, gravel & thin clay at 90'			73	137	
Yellow clay			137	139	
Blue shale			139	143	
(Use a second sheet if needed)					
18. Elevation: Topography: ____ Hill ____ Slope ____ Upland ____ Valley	19. Remarks: *Static Water Level From top of Casing (2.1') Before Bailing - 46.9' After Bailing - 48.5'		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Clarke Well & Eq., Inc. 185 Business name Address Great Bend, KS 67530 Signed <i>[Signature]</i> Date 12-12-78 Authorized representative		
6. Bore hole dia. 11 in. Completion date 8-10-78 Well depth 143 ft.			7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☒ Other Monitor			9. Casing: Material PVC Height Above or below Threaded ☐ Welded ☒ Surface 2.1' in. RMP ☐ PVC ☐ Weight 3.684 lbs./ft. Dia. 6 in. to 129 ft. depth Wall Thickness: inches or Dia. 6 in. to 143 ft. depth gage No. .280		
10. Screen: Manufacturer's name Clarke Type PVC Dia. 6" Slot/gauze 1/8" Length 10' Set between 129 ft. and 139 ft. ft. and 139 ft. Gravel pack Yes Size range of material 3/8-200			11. Static water level: * See 19 ft. below land surface Date 8-21-78 mo./day/yr.		
12. Pumping level below land surfaces: N/C ____ ft. after ____ hrs. pumping ____ g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield ____ g.p.m.			13. Water sample submitted: ____ mo./day/yr. Yes ☒ No ☐ Date 24" Dia x 2.0		
14. Well head completion: Concrete Well Cap ____ Pitless adapter ____ Inches above grade			15. Well grouted? Yes With: ☒ Neat cement ____ Bentonite ____ Concrete Depth: From 0 ft. to 126 ft.		
16. Nearest source of possible contamination: NONE ft. ____ Direction ____ Type ____ Well disinfected upon completion? ____ Yes ☒ No ☐			17. Pump: ☒ Not installed Manufacturer's name ____ Model number ____ HP ____ Volts ____ Length of drop pipe ____ ft. capacity ____ g.p.m. Type: ____ Submersible ____ Turbine ____ Jet ____ Reciprocating ____ Centrifugal ____ Other		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5