LOCATIO	ON OF WATER WELL:	FRACTION	Water Well Recor	d Form WWC-5		T		
	sedgwick	ŀ	CD	C	Section Number	Township Number	Range Number	
	d direction frem nearest town or ci	SW 1/4		S <b>W</b> 1/4	17	r 28 s	R 1W E/W	
1			•					
	O W. 47th S.		Kansas		- <del> </del>			
	-1101	ME, Bonnie				Roard of Agriculture	Divivelen of Water Persuna	
CITY STATE ZIP CODE: Classication Vancous								
	WELL'S LOCATION WITH	DEPTH OF COM		107	A FIE	Application Numb	er:	
	N SECTION BOX:	Depth(s) groundwa		1	ft. ELE'	VATION: 2 ft.	3 ft.	
1 t F		WELL'S STATIC W		_		FACE MEASURED ON mo/day/yr	3 n. 06/10/1993	
		Pump test	• .	water was		fter hours pur		
	NW NE	Est. Yield	***************************************	water was		nter nours pur after hours pur	·	
M Mile	E	Bore Hole Diameter	12 in.	to 107	ft.,	and in.	nping gpm to ft.	
= "	E	WELL WATER TO B		5 Public water			Injection well	
l . L	SW SE	1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)	
] ] ]		2 Irrigation	4 Industrial	7 Lawn and g	arden only 1(	) Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes  No X ; If yes, mo/day/yr sample was								
	S	submitted				er Well Disinfected? Yes	• •	
5 TYPE	OF CASING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS:	Glued X Clamped	
1 Steel	3 RMP (SR)		6 Asbestos-Ceme	nt 9	Other (Specify bel		Welded	
2 PVC	4 ABS		7 Fiberglass	S	DR-26	•	Threaded	
Blank casir	ng Diameter 5	in. to 87	ft., Dia	in.	to	ft., Dia in.	to ft.	
		l <b>2</b> in.,	weight 2	.35	lbs. / ft. V	Vall thickness or gauge No.	.214	
TYPE OF	SCREEN OR PERFORA	TION MATERIAL:			PVC	10 Asbestos-cen		
1 Steel	3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specif	<b>y</b> )	
2 Brass 4 Galvanized steel 6 Concrete tile				9	ABS	12 None used (o	pen hole)	
				zed wrapped	pped 8 Saw cut		11 None (open hoie)	
1 Continous slot 3 Mill slot 6 Wire wrapped					9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 87 ft. to 107 ft., From ft. to							ft.	
GRAVEL PACK INTERVALS: from 24			ft.	ft. to		ft. to	ft.	
			ft. to 107		ft., From	ft. to	ft.	
CROV	Γ MATERIAL: 1 Neat	from		. to	ft., From	ft. to	ft.	
			enient grout		tonite	4 Other		
Grout Intervals: From 4 ft. to 24 What is the nearest source of possible contamination:			ft., From	ft., From ft. to ft. 10 Livestock pens		ft., From	ft. to ft.	
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel stor		Abandon water well	
2 Sewer li			8 Sewage lagoon		12 Fertilize	- 13	15 Oil well/Gas well 16 Other (specify below)	
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit			9 Feedyard		13 Insectici	ide etorone		
1		age pit	> recujuru				e Apparent	
Direction from well?   How many feet?     FROM   TO   PLUGGING INTERVALS							RVALS	
0 3	topsoil							
3 2:	1 clay							
21 3		ıd						
37 8	6 clay							
86 89		ıd						
89 9:	3 clay							
	02 fine san	ıd						
102 1	07 grey sha	le						
<u> </u>								
<sup>7</sup> CONTR	RACTOR'S OR LANDOWNER	R'S CERTIFICATION: This	water well was (	1) <u>constructe</u>	d, (2) reconstruc	ted, or (3) plugged under r	ny jurisdiction and	
was completed on (mo/day/year)								
Well Contractor's License No								
	Vama tradation							
564						XUIU O	www www	