

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: SEDGWICK		SE 1/4 NW 1/4 NW 1/4		21		T 28 S		R 1 W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
From 47th St. So. & Tyler Road, approximately 1/4 East, So into the field. Wichita, KS.									
2 WATER WELL OWNER:		Gary Woods							
RR#, St. Address, Box # :		Rt. #1							
City, State, ZIP Code :		Clearwater, KS.							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 38 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 38 ft. below land surface measured on mo/day/yr 3-13-88.							
		Pump test data: Well water was ft. after hours pumping gpm.							
		Est. Yield gpm: Well water was ft. after hours pumping gpm.							
		Bore Hole Diameter 30 in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Transite Threaded							
Blank casing diameter 16 in. to 48 ft., Dia		in. to ft., Dia in. to ft.							
Casing height above land surface 12 in., weight 37 lbs./ft.		Wall thickness or gauge No. 3/4"							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement Transite							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 48 ft. to 100 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From ft. to ft.									
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage none apparent									
Direction from well?		How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 2 Topsoil									
2 14 Tan Clay									
14 42 Fine to Coarse Sand Fine to Coarse Gravel									
42 47 Brown Clay									
47 102 Fine to Coarse Sand Fine to Medium Gravel (loose)									
102 105 Blue Shale									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-13-88 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-31-88									
under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									