

Copy Book

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NE 1/4 Section Number 24 Township Number T 28 S Range Number R 1 E

County: SEDGWICK

Distance and direction from nearest town or city street address of well if located within city?
3245 WEST 47TH STREET SOUTH WICHITA KANSAS 67217

2 WATER WELL OWNER: CLINT PENOLLET
 RR#, St. Address, Box #: 3245 WEST 47TH ST SOUTH
 City, State, ZIP Code: WICHITA KANSAS 67217

Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 48 ft. ELEVATION: 10 ft.

Depth(s) Groundwater Encountered 1. 10 ft. 2. 10 ft. 3. 10 ft.

WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 6-4-84

Pump test data: Well water was 12 ft. after 2 hours pumping 50 gpm

Est. Yield 80 gpm: Well water was 12 ft. after 2 hours pumping 50 gpm

Bore Hole Diameter 9 in. to 45 ft., and 45 in. to 45 ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Observation well	

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	CASING JOINTS <u>Glued</u>
2 PVC	4 ABS	7 Fiberglass		Welded
				Threaded

Blank casing diameter 5 in. to 28 ft., Dia 28 in. to 28 ft., Dia 28 in. to 28 ft.

Casing height above land surface 5 in., weight 28 lbs./ft. Wall thickness or gauge No. 28

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 28 ft. to 48 ft., From 28 ft. to 48 ft., From 28 ft. to 48 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 48 ft., From 10 ft. to 48 ft., From 10 ft. to 48 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 0-3' SURFACE SOIL

Grout intervals: From 3 ft. to 10 ft., From 10 ft. to 10 ft., From 10 ft. to 10 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? WEST How many feet? 125

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	DARK SURFACE SOIL			
4	8	CLAY			
8	20	FINE SAND STRIPS OF CLAY			
20	48	FINE SAND STRIPS OF COARSE SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-4-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 437 This Water Well Record was completed on (mo/day/yr) 6-6-84 under the business name of RALPH THATZGER WALL DIGGING DRILLING (Signature) Ralph S. Thatzger

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

END

SEC:

24

NW 1/4

NE 1/4

NE 1/4

NE 1/4

NE 1/4

NE 1/4