


Copy Blotter

1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 Section Number 24 Township Number T 28 S Range Number R 1
 County: SEDGWICK
 Distance and direction from nearest town or city street address of well if located within city?
4825 SO KESSLER, WICHITA KANS

2 WATER WELL OWNER: RA. FOX 21067217
 RR#, St. Address, Box # :
 City, State, ZIP Code: 4825 SO KESSLER, WICHITA, KS Board of Agriculture, Division of Water Resources
 Application Number: NONE

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 26.5 ft. ELEVATION: 1300
 Depth(s) Groundwater Encountered 1. SEVEN ft. 2. BASEMENT ft. 3. 7/27/82 ft.
 WELL'S STATIC WATER LEVEL 7 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 30 gpm Well water was 7 NA ft. after NA hours pumping NA gpm
 Est. Yield 30 gpm Well water was 7 NA ft. after NA hours pumping NA gpm
 Bore Hole Diameter 9 in. to 7 NA ft., and 6 in. to 26.5 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 5 Public water supply ☐ 6 Oil field water supply ☐ 7 Lawn and garden only ☐ 8 Air conditioning ☐ 9 Dewatering ☐ 10 Observation well ☐ 11 Injection well ☐ 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
☐ 1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued ☐ Clamped
☐ 2 PVC ☒ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐ Welded
☐ Blank casing diameter 5 in. to 20.5 ft. Dia 1.59 in. to 20.5 ft. Dia 1.59 in. to 20.5 ft. Dia
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 209
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☒ 8 RMP (SR) ☐ 11 Other (specify)
☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☒ 7 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 20.5 ft. to 26.5 ft. From 20.5 ft. to 26.5 ft.
 GRAVEL PACK INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft.

6 GROUT MATERIAL: ☒ 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 0 ft. to 7 ft. From 7 ft. to 26.5 ft. From 26.5 ft. to 26.5 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☒ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SOUTH How many feet? 30

LITHOLOGIC LOG
 FROM TO
0 6 CLAY GRAY
6 10 SANDY CLAY BROWN
10 17 CLAY GRAY
17 26.5 SAND TAN COARSE

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/27/82 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 8/19/87
 under the business name of BEARDEN PUMP & WELL by (signature) Otis U. Bearden
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

28

R

E

SEC:

24

N

E

W

S