


1 LOCATION OF WATER WELL: Sedgwick		FRACTION NE SE NW NW		Section Number 24		Township Number T 28 S		Range Number R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city? 4900 S. Kessler Wichita, Kansas									
2 WATER WELL OWNER: DORE, Dave		Board of Agriculture, Division of Water Resource							
RR#, ST. ADDRESS, BOX #: 4900 S. Kessler		Application Number:							
CITY, STATE, ZIP CODE: Wichita, Kansas									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 50 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 08/17/1992 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 50 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No							
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass		8 Concrete tile 9 Other (Specify below) SDR-26		CASING JOINTS: Glued ☒ Clamped Welded Threaded			
Blank casing Diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214									
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel		5 Fiberglass 6 Concrete tile		7 PVC 8 RMP (SR) 9 ABS		10 Asbestos-cement 11 other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut		8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)					
SCREEN-PERFORATION INTERVALS: from 30 ft. to 50 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 24 ft. to 50 ft., From ft. to ft. from ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage		14 Abandon water well 15 Oil well/Gas well 16 Other (specify below) None Apparent					
Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS		How many feet?							
0 2 topsoil									
2 10 clay									
10 24 sand clay									
24 50 medium to coarse sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/17/1992 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/30/92 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>									
143									