

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction: SE 1/4 SW 1/4 SW 1/4	Section Number: 26	Township Number: T 28 S	Range Number: R 1 E
Distance and direction from nearest town or city street address of well if located within city? 63rd + HAWK					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Vulcan Materials Co. P. O. Box 12283 Wichita, Ks. 67233 MW 21-C Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to 58 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 2 in. to 48 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 30 in. weight lbs./ft. Wall thickness or gauge No.			
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 <u>Stainless steel</u> 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 <u>Wire wrapped</u> 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 48 ft. to 58 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 46 ft. to 58 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other Grout Intervals: From 0 ft. to 48 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) FRANT 13 Insecticide storage How many feet? 3500			
Direction from well? W					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	5	gray and white sand/clay			
5	10	compact poorly sorted sand			
10	15	loose med. gravel			
15	20	med. loose yellow sand			
20	25	yellow & red coarse sand			
25	30	orange coarse sand			
30	35	yellow fine gravel			
35	45	yellow med. sand			
45	50	coarse sand/fine gravel			
50	55	fine to med. gravel			
55	58'3"	med-coarse yellow & red sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/30/90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 2/15/90 under the business name of Layne Western co., Inc., Wichita, Ks. by (signature) [Signature] B. Meier					