


LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 SW 1/4 Section Number 30 Township Number T 28 S Range Number R 1 E
 Distance and direction from nearest town or city street address of well if located within city? 12 West 2 3/4 South Schulte St.

WATER WELL OWNER: McAlister Drilling
 St. Address, Box #: 251 No Water Supply #102
 City, State, ZIP Code: Williston ND 58102

Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL: 15 ft. ELEVATION: 12-12-83
 Depth(s) Groundwater Encountered: 1 ft. 35 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 35 ft. below land surface measured on mo/day/yr 12-12-83
 Pump test data: Well water was 40 ft. after 12 hours pumping 20 gpm
 Est. Yield 30 gpm: Well water was 40 ft. after 12 hours pumping 20 gpm
 Bore Hole Diameter: 11 in. to 15 in. and 15 in. to 15 in.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)
 2 PVC 4 ABS

5 Wrought iron 8 Concrete tile
 6 Asbestos-Cement 9 Other (specify below)
 7 Fiberglass

CASING JOINTS: Glued X Clamped
 Welded
 Threaded

Blank casing diameter: 5 in. to 12 in. Dia. 1.59 in. to 1.59 in. Dia. 1.59 in. to 1.59 in. Dia. 1.59 in. to 1.59 in. Dia.
 Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SAP-26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 7 PVC
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR)
 9 ABS

10 Asbestos-cement 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot
 2 Louvered shutter 4 Key punched

5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 80 ft. to 95 ft. From 80 ft. to 95 ft. From 80 ft. to 95 ft. From 80 ft. to 95 ft.
 GRAVEL PACK INTERVALS: From 15 ft. to 95 ft. From 15 ft. to 95 ft. From 15 ft. to 95 ft. From 15 ft. to 95 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 0 ft. to 15 ft. From 15 ft. to 15 ft. From 15 ft. to 15 ft. From 15 ft. to 15 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy
 2 Sewer lines 5 Cess pool 8 Sewage lagoon
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard

10 Livestock pens 14 Abandoned water well
 11 Fuel storage 15 Oil well/Gas well
 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? N.W. How many feet? 125 Drilled

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top So.			
2	28	C/HY.			
28	40	PROP SAND			
40	43	C/HY.			
43	78	PROP SAND			
78	94	C/HY.			
94	95	PROP SAND			

RECEIVED

JUN 10 1985

BUREAU OF OIL FIELD & ENVIRONMENTAL GEOLOGY

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-12-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 12-12-83

Under the business name of McAlister Drilling by (signature) McAlister

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.