

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>SEDGWICK</u>		NW 1/4 SE 1/4 SW 1/4	33	T 28 S	R 1 W EW
Distance and direction from nearest town or city street address of well if located within city? <u>6601 South Ridge Road</u> <u>Wichita, Kansas</u>					
2) WATER WELL OWNER:		Air Products & Chemical Co.			
RR#, St. Address, Box # :		6601 south Ridge Road			
City, State, ZIP Code :		Wichita, Kansas			
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: <u>95</u> ft. ELEVATION: <u>10-20-86</u> ft.			
		Depth(s) Groundwater Encountered 1. <u>28</u> ft. 2. <u>10-20-86</u> ft. 3. <u>10-20-86</u> ft.			
		WELL'S STATIC WATER LEVEL <u>28</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm			
		Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm			
		Bore Hole Diameter _____ in. to _____ ft., and _____ in. to _____ ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes _____ No _____; If yes, mo/day/yr sample was submitted _____			
5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued _____ Clamped _____			
1 Steel <u>3 RMP (SR)</u>		5 Wrought iron 8 Concrete tile			
2 PVC <u>4 ABS</u>		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter <u>5</u> in. to _____ ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft.		7 Fiberglass _____ Threaded _____			
Casing height <u>above</u> land surface <u>3'</u> below _____ in., weight _____ lbs./ft. Wall thickness or gauge No. _____					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) _____					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) _____					
SCREEN-PERFORATED INTERVALS: From _____ ft. to _____ ft., From _____ ft. to _____ ft.					
GRAVEL PACK INTERVALS: From _____ ft. to _____ ft., From _____ ft. to _____ ft.					
6) GROUT MATERIAL: 1 Neat cement 2 <u>Cement</u> grout 3 Bentonite 4 Other _____					
Grout Intervals: From <u>3</u> ft. to <u>10</u> ft., From <u>10</u> ft. to <u>20</u> ft., From _____ ft. to _____ ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage <u>none</u>					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
95	20	Sand and Gravel			
20	10	Bentonite Grout			
10	3	Cement grout			
3	0	Topsoil			
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged under</u> my jurisdiction and was completed on (mo/day/year) <u>10-20-86</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>236</u> This Water Well Record was completed on (mo/day/yr) <u>5-22-87</u> under the business name of <u>Harp Well & Pump Service, Inc.</u> by (signature) <u>Mary Arnold</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					