

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number																																																																																																
County: Sedgwick		NE ¼ NW ¼ NE ¼	34	T 28 S	R 1 EW																																																																																																
Distance and direction from nearest town or city street address of well if located within city? 4000' E-SE 6200 S. Ridge Road; Wichita, KS 40875106 MW-3B (East Well)																																																																																																					
2 WATER WELL OWNER: Vulcan Chemicals RR#, St. Address, Box #: P.O. Box 12283 City, State, ZIP Code: Wichita, KS 67277 Board of Agriculture, Division of Water Resources Application Number:																																																																																																					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: Approx. Surface 1305 Depth(s) Groundwater Encountered 1. 49 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 44.5 ft. below land surface measured on mo/day/yr 10/28/87 Pump test data: Well water was ft. after hours pumping gpm Est. Yield N/A gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8.5 in. to 80 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X																																																																																																			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass 316 Stainless Steel Threaded X Blank casing diameter 2 in. to 70 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 28 in., weight lbs./ft. Wall thickness or gauge No. Schedule 5/40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 316 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 68 ft. to 80 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																																																					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 58 ft., From 58 ft. to 68 ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Landfill Direction from well? East-Southeast How many feet? 1700																																																																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> </tr> </thead> <tbody> <tr> <td>0'</td> <td>11'</td> <td>Brown Lean to Fat Clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>11'</td> <td>17'</td> <td>Red-Brown Lean Clay With Sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td>17'</td> <td>26'</td> <td>Brown Fine to Medium Sand With Clay Seams</td> <td></td> <td></td> <td></td> </tr> <tr> <td>26'</td> <td>39.5'</td> <td>Red-Brown Fine to Coarse Sand With Clay Seams</td> <td></td> <td></td> <td></td> </tr> <tr> <td>39.5'</td> <td>65.5'</td> <td>Red-Gray Fine to Medium Sand With Clay Seams</td> <td></td> <td></td> <td></td> </tr> <tr> <td>65.5'</td> <td>72'</td> <td>Gray Silty Lean to Fat Clay With Sand Seams</td> <td></td> <td></td> <td></td> </tr> <tr> <td>72'</td> <td>79.5'</td> <td>Red-Brown Fine to Coarse Sand and Gravel</td> <td></td> <td></td> <td></td> </tr> <tr> <td>79.5'</td> <td>91.5'</td> <td>Gray Lean Clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>91.5'</td> <td>97.5'</td> <td>Brown Medium to Coarse Sand and Gravel</td> <td></td> <td></td> <td></td> </tr> <tr> <td>97.5'</td> <td>98.5'</td> <td>Gray Weathered Shale</td> <td></td> <td></td> <td></td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	0'	11'	Brown Lean to Fat Clay				11'	17'	Red-Brown Lean Clay With Sand				17'	26'	Brown Fine to Medium Sand With Clay Seams				26'	39.5'	Red-Brown Fine to Coarse Sand With Clay Seams				39.5'	65.5'	Red-Gray Fine to Medium Sand With Clay Seams				65.5'	72'	Gray Silty Lean to Fat Clay With Sand Seams				72'	79.5'	Red-Brown Fine to Coarse Sand and Gravel				79.5'	91.5'	Gray Lean Clay				91.5'	97.5'	Brown Medium to Coarse Sand and Gravel				97.5'	98.5'	Gray Weathered Shale																																	
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG																																																																																																
0'	11'	Brown Lean to Fat Clay																																																																																																			
11'	17'	Red-Brown Lean Clay With Sand																																																																																																			
17'	26'	Brown Fine to Medium Sand With Clay Seams																																																																																																			
26'	39.5'	Red-Brown Fine to Coarse Sand With Clay Seams																																																																																																			
39.5'	65.5'	Red-Gray Fine to Medium Sand With Clay Seams																																																																																																			
65.5'	72'	Gray Silty Lean to Fat Clay With Sand Seams																																																																																																			
72'	79.5'	Red-Brown Fine to Coarse Sand and Gravel																																																																																																			
79.5'	91.5'	Gray Lean Clay																																																																																																			
91.5'	97.5'	Brown Medium to Coarse Sand and Gravel																																																																																																			
97.5'	98.5'	Gray Weathered Shale																																																																																																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/15/87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. under the business name of by (signature)																																																																																																					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.																																																																																																					