

1 LOCATION OF WATER WELL:		Fraction		Form WWC-5		RSA 82a-1212			
County: Sedgwick		SW 1/4 NW 1/4 NW 1/4		Section Number 13		Township Number T 28 S		Range Number R 1	
Distance and direction from nearest town or city street address of well if located within city?									
4200 South West Street, Wichita, Kansas									
2 WATER WELL OWNER:		D & D Equipment/Duling Construction		01948026		MW-1			
RR#, St. Address, Box # :		4200 South West Street		Board of Agriculture, Division of Water Resources					
City, State, ZIP Code :		Wichita, Kansas 67217		Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 18.5 ft. ELEVATION: Approx. 1281.0							
1 Mile W E S N X NW NE SW SE		Depth(s) Groundwater Encountered 1. 13.5 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 12.8 ft. below land surface measured on mo/day/yr 09/21/94							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 8.25 in. to 18.50 ft., and in. to ft.							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded X							
Blank casing diameter 2 in. to 8.5 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface -3 in. weight lbs./ft. Wall thickness or gauge No. Schedule 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 8.5 ft. to 18.5 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 6.5 ft. to 18.5 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 4 ft. From 4 ft. to 6 ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage UST									
Direction from well?		How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0.0 2.0 Topsoil									
2.0 5.0 Brown, Lean to Fat Clay									
5.0 9.0 Brown, Silty Lean Clay									
9.0 13.0 Brown, Sandy Lean Clay									
13.0 18.5 Gray, Fine to Medium Sandy With Clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/13/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10/10/94 under the business name of Terracon Consultants, Inc. by (signature) Steve Lisich									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									