

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 1 Township Number T 28 S Range Number R 1 EW

Distance and direction from nearest town or city street address of well if located within city?  
Town & Country, Pawnee and West Street, Wichita, Kansas

2 WATER WELL OWNER: Town & Country Markets 01948032 MW-6  
RR#, St. Address, Box #: P.O. Box 17087 Board of Agriculture, Division of Water Resources  
City, State, ZIP Code: Wichita, Kansas 67217 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with 'X' in the NW and NE quadrants. Labels N, S, E, W and 1 Mile are present.]

4 DEPTH OF COMPLETED WELL: 18.5 ft. ELEVATION: Approx. 1290.0  
Depth(s) Groundwater Encountered 1. 12.0 ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL: 11/05 ft. below land surface measured on mo/day/yr 10/14/94  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield N/A gpm: Well water was ft. after hours pumping gpm  
Bore Hole Diameter: 8.25 in. to 18.5 ft., and in. to ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter: 2 in. to 7 ft., Dia. in. to ft., Dia. in. to ft.  
Casing height above land surface: -3 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40  
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft. From ft. to ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 5 ft. to 17 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 5 ft., From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
UST  
13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.8	Gravel			
0.8	3.5	Dark Brown Lean Clay			
3.5	4.5	Gray-Brown, Lean to Fat Clay			
4.5	9.0	Gray-Brown, Silty Lean Clay			
9.0	18.5	Brown, Fine to Coarse Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/05/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10/27/94 under the business name of Terracon Consultants, Inc. by (signature) Steve Fisher