


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW 1/4 SW 1/4 SE 1/4		Section Number 7	Township Number T 28 S	Range Number R 1 EW																																																												
Distance and direction from nearest town or city street address of well if located within city? 11012 S.W. BLVD SHULTE KS WEST M.W.#1																																																																		
2 WATER WELL OWNER: JIM PETERS RR#, St. Address, Box # : 11012 SW BLVD City, State, ZIP Code : SHULTE, KS 67215 Board of Agriculture, Division of Water Resources Application Number:																																																																		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S 		4 DEPTH OF COMPLETED WELL: 30' ft. ELEVATION: Depth(s) Groundwater Encountered 24 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/2 in. to 30 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																																																
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 15 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface -0.3 in., weight shed 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 2 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot X3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 30 ft. to 15 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 30 ft. to 14 ft. From ft. to ft. From ft. to ft. From ft. to ft.																																																																		
6 GROUT MATERIAL: 1 Neat cement X2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 13 ft. to 0.6 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon X1 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SW How many feet? 210																																																																		
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.6</td> <td>CONCRETE</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.6</td> <td>3</td> <td>TOPSOIL</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>8</td> <td>BRN CLAY</td> <td></td> <td></td> <td></td> </tr> <tr> <td>8</td> <td>15</td> <td>PLASTIC BRN CLAY</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>18</td> <td>BRN TO TAN CLAY W FINE SAND</td> <td></td> <td></td> <td></td> </tr> <tr> <td>18</td> <td>20</td> <td>" " " "</td> <td></td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>25</td> <td>FINE TO MEDIUM GRAINED SAND SATURATED AT 24'</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25</td> <td>30</td> <td>MEDIUM G. SAND</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6" style="text-align:center; height: 50px;">Variance Requested</td> </tr> </tbody> </table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	0.6	CONCRETE				0.6	3	TOPSOIL				3	8	BRN CLAY				8	15	PLASTIC BRN CLAY				15	18	BRN TO TAN CLAY W FINE SAND				18	20	" " " "				20	25	FINE TO MEDIUM GRAINED SAND SATURATED AT 24'				25	30	MEDIUM G. SAND				Variance Requested					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																													
0	0.6	CONCRETE																																																																
0.6	3	TOPSOIL																																																																
3	8	BRN CLAY																																																																
8	15	PLASTIC BRN CLAY																																																																
15	18	BRN TO TAN CLAY W FINE SAND																																																																
18	20	" " " "																																																																
20	25	FINE TO MEDIUM GRAINED SAND SATURATED AT 24'																																																																
25	30	MEDIUM G. SAND																																																																
Variance Requested																																																																		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-10-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 1-11-95 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature) 